

**Dotco Tools.
Designed for
Versatility.**



COOPER Tools

Application and Design Versatility

Dotco offers the right tool for every abrasive application.

Application Versatility

With only a few motor types, a diverse line of Dotco tools has been developed to handle a wide range of applications. If you need to drill, sand, grind, buff, polish, scribe, drive, route, chamfer, saw, nibble, shear or shave, Dotco is your choice solution.

Design Versatility

The Dotco line of tools is designed with high interchangeability of parts which means reduced repair parts inventories for you. And due to this commonality of design, tools are easier to repair.

Performance Versatility

For the past 50 years Dotco has built a reputation of producing quality material removal tools that



are durable, dependable and versatile. Today, Dotco is the premier line of material removal tools in the industrial marketplace. A position maintained by producing tools that are small, comfortable and light-weight, yet capable of withstanding tough treatment no matter the application.

Designed for Ergonomics

Form follows function in the design of Dotco tools. For operator comfort Dotco tools work *with*, not against. Features like light weight, elastomer housings, low vibration, and low noise help make Dotco the favorite among operators.



Dotco's Original Patented Features

Dotco tools have many original patented features. Our lubrication wick system is designed to extend gear life, increase performance, and reduce downtime.



Precision parts

Without precision parts you can not have good, reliable tools to manufacture quality products. No matter if it's a spindle, a chuck, a motor or an angle head, Dotco parts are manufactured from the finest materials available and are machined to the highest tolerances.

Low noise, low vibration

Reduced noise and vibration of power tools are important issues. Dotco tools are designed to operate as quietly as possible, while providing substantial power. Vibration is kept to a minimum by using precision parts and high quality bearings.

Oilless Blades

Many Dotco tools can be run with optional oilless blades which require only half the lubrication of standard blades. Just another way we help you make the best products possible.

Rapid Select means fast delivery

Models indicated with the **Rapid Select** icon represent our most popular tools, and are available for fast delivery on limited quantities.



Dotco Options

Tools must be ordered with a lock-off lever throttle to be CE compliant. To order a Lock-off lever throttle, simply substitute "S" for "L" in the model number for 12 Series tools and "K" for "D" in 10 Series tools.

Geared or Gearless Heads

Silver Heads are Gearless
Black Heads are Geared



0.06, 0.1, & 0.2 HP Industrial Duty Tools: Precision Turbines, Carbide Bur Grinders, Mounted Wheel Grinders

Feather touch cutting control. Extra high speed, powerful and cool running. Surgically precise hand machining of

intricate parts. Light, responsive, whisper quiet. Industry proven for production duty.



10-90 Series 0.06 hp Front Exhaust Precision Turbines

Model No.	Exh.	Abrasive Capacity	Free Speed	Weight		Length		Collet Size
			rpm	lbs.	kgs	mm	in.	
10-90 Series - 0.06 hp (0.044 kW) - Front Exhaust								
10R9000-03	F	3/16" Carbide Bur, 3/16" Diamond Pin	100,000	0.5	0.2	5.4	137	3mm
10R9000-08	F	3/16" Carbide Bur, 3/16" Diamond Pin	100,000	0.5	0.2	5.4	137	1/8"

12-91 Series 0.1 hp Rear Exhaust Governed Precision Turbines

Model No.	Exh.	Abrasive Capacity	Free Speed	Weight		Length		Collet Size
			rpm	lbs.	kgs	mm	in.	
12-91 Series - 0.1 hp (0.074 kW) - Rear Exhaust W/O Overhose								
12R9180-03	R	1/8" Carbide Bur, 1/8" Diamond Pin	65,000	0.4	0.2	5.8	147	3mm
12R9180-08	R	1/8" Carbide Bur, 1/8" Diamond Pin	65,000	0.4	0.2	5.8	147	1/8"

12-03, 10-04, 12-04 Series 0.1 hp Rear Exhaust Precision Grinders

Model No.	W/Collet Guard	W/O Collet Guard	Wrenchless Chuck	Abrasive Capacity	Free Speed	Weight		Length		Collet Size
					rpm	lbs.	kgs	mm	in.	
12-03 Series - 0.1 hp (0.074 kW) - Gearless Rear Exhaust										
12R0380-13				1/4" Carbide Bur, 1/4" Diamond Pin	80,000	0.3	0.1	5.5	140	3mm
12R0380-18				1/4" Carbide Bur, 1/4" Diamond Pin	80,000	0.3	0.1	5.5	140	1/8"
10-04 Series - 0.1 hp (0.074 kW) - Rear Exhaust										
10R0401-13				1/4" Carbide Bur, 1/4" Diamond Pin	60,000	0.2	0.1	5.8"	147"	3mm
10R0401-18				1/4" Carbide Bur, 1/4" Diamond Pin	60,000	0.2	0.1	5.8"	147"	1/8"
12-04 Series - 0.1 hp (0.074 kW) - Rear Exhaust										
12R0410-13				1/4" Carbide Bur, 1/4" Diamond Pin	60,000	0.3	0.1	5.8	147	3mm
12R0410-18				1/4" Carbide Bur, 1/4" Diamond Pin	60,000	0.3	0.1	5.8	147	1/8"
12-04 Series - 0.1 hp (0.074 kW) - Rear Exhaust with 4' Overhose										
12R0410-43				1/4" Carbide Bur, 1/4" Diamond Pin	60,000	0.3	0.1	5.8	147	3mm
12R0400-13				1/4" Carbide Bur, 1/4" Diamond Pin	60,000	0.3	0.1	5.8	147	3mm
12R0400-18				1/4" Carbide Bur, 1/4" Diamond Pin	60,000	0.3	0.1	5.8	147	1/8"

* For length of 10R0412 wrenchless chuck models, add 0.4" (10mm)

12-05 Series 0.2 hp Carbide Bur or Mounted Wheel Grinder with Collet Guard

Model No.	Exh.	Abrasive Capacity	Free Speed	Weight		Length		Collet Size
			rpm	lbs.	kgs	mm	in.	
12-05 Series - 0.2 hp (0.15 kW) - with Collet Guard - Rear Exhaust								
12R0500-36	F	1/4" Carbide Bur, 7/8" Mtd. Wheel	40,000	0.7	0.3	5.9	150	1/4"(300)

Notes: Models indicated with the Rapid Select icon represent our most popular tools, and are available for fast delivery on limited quantities.

Exhaust: F-Front Exhaust

R-Rear Exhaust

S-Side Exhaust

Tools m

0.3 HP Standard Duty Tools: Carbide Bur Grinders, Mounted Wheel Grinders, Disc Sanders, Flutter Disc Sanders, Belt Sanders, Routers

Beautifully balanced and exceptionally powerful for their size. Easily handle work of larger, cumbersome electrics. Precision, extra smooth spindles deliver

superior workpiece quality for higher operator productivity.



12L1382-36B2
Belt Sander

12L1092-01FD
Flutter Disk

12L1180-36
Carbide Bur or
Mounted Wheel
Grinder

10L1080-36
Carbide Bur or
Mounted Wheel
Grinder

12L1001-36RT
Router

12L1001-36
Carbide Bur or
Mounted Wheel
Grinder

12L1380-36
Carbide Bur or
Mounted Wheel
Grinder

12L1281-36
Carbide Bur or
Mounted Wheel
Grinder

10L1201-36
Disk Sander

10-10 & 12-10 Series 0.3 hp Carbide Bur/Mounted Wheel Grinders

Model No.	Exh.	Abrasives Capacity	Free Speed		Weight		Length		Collet Size
			rpm		lbs.	kgs	in.	mm	
10-10 Series (K&L) - 0.3 hp (0.22 kW) - 300 Series Collet									
10K1080-36	R	1/2" Carbide Bur, 1" Mt. Wheel	30,000	0.7	0.31	4.6	117	1/4"	
10L1001-36	F	1/2" Carbide Bur, 1" Mt. Wheel	34,000	0.7	0.31	4.6	117	1/4"	
10L1000-36	F	1/2" Carbide Bur, 1" Mt. Wheel	30,000	0.7	0.31	4.6	117	1/4"	
10L1003-36	F	1/2" Carbide Bur, 1" Mt. Wheel	25,000	0.7	0.31	4.6	117	1/4"	
10L1081-36	R	1/2" Carbide Bur, 1" Mt. Wheel	34,000	0.7	0.31	4.6	117	1/4"	
10L1080-36	R	1/2" Carbide Bur, 1" Mt. Wheel	30,000	0.7	0.31	4.6	117	1/4"	
10L1082-36	R	1/2" Carbide Bur, 1" Mt. Wheel	25,000	0.7	0.31	4.6	117	1/4"	
12-10 Series - 0.3 hp (0.22 kW) - 300 Series Collet									
12L1001-36	F	1/2" Carbide Bur, 1" Mt. Wheel	34,000	0.8	0.4	6.0	152	1/4"	
12L1000-36	F	1/2" Carbide Bur, 1" Mt. Wheel	30,000	0.8	0.4	6.0	152	1/4"	
12L1003-36	F	1/2" Carbide Bur, 1" Mt. Wheel	25,000	0.8	0.4	6.0	152	1/4"	
12L1081-36	R	1/2" Carbide Bur, 1" Mt. Wheel	34,000	0.8	0.4	6.0	152	1/4"	
12L1080-36	R	1/2" Carbide Bur, 1" Mt. Wheel	30,000	0.8	0.4	6.0	152	1/4"	
12L1082-36	R	1/2" Carbide Bur, 1" Mt. Wheel	25,000	0.8	0.4	6.0	152	1/4"	
12-10 Series - 0.3 hp (0.22 kW) - 300 Series Collet									
12S1001-36	F	1/2" Carbide Bur, 1" Mt. Wheel	34,000	0.8	0.4	6.0	152	1/4"	
12S1000-36	F	1/2" Carbide Bur, 1" Mt. Wheel	30,000	0.8	0.4	6.0	152	1/4"	
12S1003-36	F	1/2" Carbide Bur, 1" Mt. Wheel	25,000	0.8	0.4	6.0	152	1/4"	
12S1081-36	R	1/2" Carbide Bur, 1" Mt. Wheel	34,000	0.8	0.4	6.0	152	1/4"	
12S1080-36	R	1/2" Carbide Bur, 1" Mt. Wheel	30,000	0.8	0.4	6.0	152	1/4"	
12S1082-36	R	1/2" Carbide Bur, 1" Mt. Wheel	25,000	0.8	0.4	6.0	152	1/4"	

12-10 Series 0.3 hp Flutter Disc

Model No.	Exh.	Abrasive Sheet Capacity	Free Speed		Weight		Length		Collet Size
			rpm		lbs.	kgs	mm	in.	
12-10 Series - 0.3 hp (0.22 kW) - Flutter Disc									
12L1092-01FD	R	2" x 41/2"	3,200	1.5	0.7	9.3	236	1/2" Arbor	

10-12 & 12-12 Series 0.3 hp Disc Sanders or 1/2" Carbide Bur, 1" Mt. Wheel Grinders

Model No.	Exh.	Abrasives Capacity	Free Speed		Weight		Head Height		Length		Collet Size
			rpm		lbs.	kgs	in.	mm	in.	mm	
10-12 Series - 0.3 hp (0.22 kW) - 300 Series Collet											
10L1200-36	F	3" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	12,000	0.98	0.45	2.9	74	5.0	127	1/4"	
10L1201-36	F	2" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	20,000	0.98	0.45	2.9	74	5.0	127	1/4"	
10L1281-36	R	2" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	20,000	0.98	0.45	2.9	74	5.0	127	1/4"	
10L1280-36	R	3" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	12,000	0.98	0.45	2.9	74	5.0	127	1/4"	
12-12 Series - 0.3 hp (0.22 kW) - 300 Series Collet											
12L1200-36	F	3" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	12,000	1.1	0.5	2.9	74	6.3	160	1/4"	
12L1201-36	F	2" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	20,000	1.1	0.5	2.9	74	6.3	160	1/4"	
12L1280-36	R	3" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	12,000	1.1	0.5	2.9	74	6.3	160	1/4"	
12L1281-36	R	2" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	20,000	1.1	0.5	2.9	74	6.3	160	1/4"	
12-12 Series - 0.3 hp (0.22 kW) - 300 Series Collet											
12S1200-36	F	3" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	12,000	1.1	0.5	2.9	74	6.3	160	1/4"	
12S1200-36M6	F	3" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	12,000	1.1	0.5	2.9	74	6.3	160	6mm	
12S1201-36	F	2" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	20,000	1.1	0.5	2.9	74	6.3	160	1/4"	
12S1280-36	R	3" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	12,000	1.1	0.5	2.9	74	6.3	160	1/4"	
12S1281-36	R	2" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	20,000	1.1	0.5	2.9	74	6.3	160	1/4"	

12-13 Series 0.3 hp Gearless Belt Sander

Model No.	Exh.	Sanding Belt Capacity	Free Speed		Weight		Length	
			rpm		lbs.	kgs	in.	mm
12-13 Series - 0.3 hp (0.22 kW) - Gearless with Sanding Belt								
12L1382-36B2	R	1/2" x 12"	20,000	1.4	0.6	11.3	287	

12-13 Series 0.3 hp Gearless Disc Sanders or 1/2" Carbide Bur, 1" Mt. Wheel Grinders

Model No.	Exh.	Abrasives Capacity	Free Speed		Weight		Head Height		Length		Collet Size
			rpm		lbs.	kgs	in.	mm	in.	mm	
12-13 Series - 0.3 hp (0.22 kW) - Gearless, 300 Series Collet											
12L1302-36	F	2" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	20,000	1.1	0.5	3.7	94	7.1	180	1/4"	
12L1380-36	R	1" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	30,000	1.1	0.5	3.7	94	7.1	180	1/4"	
12L1381-36	R	2" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	25,000	1.1	0.5	3.7	94	7.1	180	1/4"	
12L1382-36	R	2" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	20,000	1.1	0.5	3.7	94	7.1	180	1/4"	
12S1302-36	F	2" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	20,000	1.1	0.5	3.7	94	7.1	160	1/4"	
12S1382-36	R	2" Sanding Disc, 1/2" Carbide Bur, 1" Mt. Wheel	20,000	1.1	0.5	3.7	94	7.1	180	1/4"	

0.5, 0.6 & 0.9 HP Medium Duty Tools: Carbide Bur Grinders, Mounted Wheel Grinders, Cone or Plug Wheel Grinders, Cut-Off Wheel Grinders, Sanders, Polishers, Buffers, Routers

High power productivity in a midsize air tool.
Aggressive cutting action through a wide range of

grinding duties in these 0.5, 0.6,
& 0.9 hp models.



12L2580-01
Carbide Bur or Mounted Wheel Grinder

12L2580-01RT
Router

12L2718-28
Cut-Off Wheel Grinder

12S2600-77
Cone / Plug Wheel Grinder

10L2500-01
Carbide Bur or Mounted Wheel Grinder

12L2384-01
Grinder

12L2762-80
Buffer, Polisher or Sander

12-23 Series 0.5 hp Gearless Carbide Bur/Mounted Wheel Grinder

Model No.	Exh.	Abrasives Capacity	Free Speed rpm	Weight lbs. kgs	Head Height in. mm	Length in. mm	Collet Size
12-23 Series - 0.5 hp (.38kW) - Gearless, 200 Series Collet							
12L2384-01	F	3/4" Carbide Bur, 1-1/4" Mounted Wheel	20,000	2.0 .91	5.5 140	7.5 190	1/4"

12-20, 10-25 & 12-25 Series 0.6 & 0.9 hp Carbide Bur/Mounted Wheel Grinders

Model No.	Exh.	Abrasives Capacity	Free Speed rpm	Weight lbs. kgs	Length in. mm	Collet Size
12-20 Series - 0.6 hp (0.45 kW) - 200 Series Collet						
12L2000-01	F	3/4" Carbide Bur, 1-1/2" Mtd. Wheel	25,000	1.4 0.6	6.9 175	1/4"
12L2001-01	F	3/4" Carbide Bur, 1-1/2" Mtd. Wheel	20,000	1.4 0.6	6.9 175	1/4"
12L2002-01	F	3/4" Carbide Bur, 1-1/2" Mtd. Wheel	18,000	1.4 0.6	6.9 175	1/4"
12L2080-01	R	3/4" Carbide Bur, 1-1/2" Mtd. Wheel	25,000	1.4 0.6	6.9 175	1/4"
12L2081-01	R	3/4" Carbide Bur, 1-1/2" Mtd. Wheel	20,000	1.4 0.6	6.9 175	1/4"
12L2082-01	R	3/4" Carbide Bur, 1-1/2" Mtd. Wheel	18,000	1.4 0.6	6.9 175	1/4"
12-20 Series - 0.6 hp (0.45 kW) - 300 Series Collet						
12L2000-36	F	3/4" Carbide Bur, 1-1/2" Mtd. Wheel	25,000	1.4 0.6	7.5 191	1/4"
12L2080-36	R	3/4" Carbide Bur, 1-1/2" Mtd. Wheel	25,000	1.4 0.6	7.5 191	1/4"
10-25 & 12-25 Series - 0.9 hp (0.67 kW) - 200 Series Collet						
10L2500-01	F	1" Carbide Bur, 1-1/2" Mtd. Wheel	23,000	1.4 0.6	6.3 159	1/4"
12L2500-01	F	1" Carbide Bur, 1-1/2" Mtd. Wheel	23,000	1.8 0.8	7.3 185	1/4"
12L2502-01	F	1" Carbide Bur, 1-1/2" Mtd. Wheel	18,000	1.8 0.8	7.3 185	1/4"
12L2562-01	F	1" Carbide Bur, 1-1/2" Mtd. Wheel	12,000*	1.8 0.8	7.4** 188**	1/4"
12L2580-01	R	1" Carbide Bur, 1-1/2" Mtd. Wheel	23,000	1.8 0.8	7.3 185	1/4"
12L2582-01	R	1" Carbide Bur, 1-1/2" Mtd. Wheel	18,000	1.8 0.8	7.3 185	1/4"
12-25 Series - 0.9 hp (0.67 kW) - 300 Series Collet						
12L2500-36	F	1" Carbide Bur, 1-1/2" Mtd. Wheel	23,000	1.8 0.8	8.0 203	1/4"

* Governor controlled speeds
** Front exhaust governor control models, add 0.7" (18mm)

12-22 Series 0.6 hp Carbide Bur/Mounted Wheel Grinders

Model No.	Exh.	Abrasives Capacity	Free Speed rpm	Weight lbs. kgs	Head Height in. mm	Length in. mm	Collet Size
12-22 Series - 0.6 hp (0.45 kW) - 300 Series Collet							
12L2218-36	R	1/2" Carbide Bur, 1" Mtd. Wheel	18,000	1.7 0.8	2.7 69	7.5 191	1/4"

12-26 Series 0.9 hp Cone or Plug Wheel Grinders

Model No.	Exh.	Abrasive Capacity	Free Speed rpm	Weight lbs. kgs	Length in. mm	Spindle Size
12-26 Series - 0.9 hp (0.67 kW) - 6" (152mm) Extension						
12S2600-77	S	1-1/4" Cone or Plug Wheel	23,000	2.9 1.3	12.5 318	3/8" - 24

12-27 Series 0.9 hp Cut-Off Wheel Grinders

Model No.	Exh.	Type I Cut-off Wheel Capacity	Free Speed rpm	Weight lbs. kgs	Length in. mm	Arbor Size
12-27 Series - 0.9 hp (0.67 kW)						
12L2718-28	R	4"	18,000	3.2 1.5	8.0 203	3/8"

10-27 & 12-27 Series 0.9 hp Right Angle Sanders

Model No.	Exh.	Sanding Disc Capacity	Free Speed rpm	Weight lbs. kgs	Head Height in. mm	Length in. mm	Spindle Size
10-27 - Series - 0.9 hp (0.67 kW) - 5/8"- 11 External Threaded Spindle							
10L2750-80	F	7"	6,000	3.11 1.41	3.9 99	8.5 216	5/8"-11"
10L2751-80	F	5"	9,000	3.08 1.4	3.9 99	8.5 216	5/8"-11"
12-27 - Series - 0.9 hp (0.67 kW) - 5/8"- 11 Threaded Spindle							
12L2750-80	F	7"	6,000	3.4 1.5	3.9 99	9.8 249	5/8"-11"
12L2751-80	F	5"	9,000	3.4 1.5	3.9 99	9.8 249	5/8"-11"
12L2752-80	F	4"	11,000	3.4 1.5	3.9 99	9.8 249	5/8"-11"
12L2760-80	F	7"	3,300**	3.3 1.8	3.9 99	10.5 267	5/8"-11"
12L2761-80	F	7"	6,000	3.3 1.8	3.9 99	10.5 267	5/8"-11"
12L2762-80	F	7"	4,500**	3.3 1.8	3.9 99	10.5 267	5/8"-11"
12L2788-80	R	7"	2,200	3.4 1.5	3.9 99	11.7 297	5/8"-11"
12-27 - Series - 0.9 hp (0.67 kW) - 5/8"- 11 Threaded Spindle							
12S2750-80	F	7"	6,000	3.4 1.5	3.9 99	9.8 249	5/8"-11"
12S2751-80	F	5"	9,000	3.4 1.5	3.9 99	9.8 249	5/8"-11"
12S2752-80	F	4"	11,000	3.4 1.5	3.9 99	9.8 249	5/8"-11"
12S2762-80	F	7"	4,500**	3.3 1.8	3.9 99	10.5 267	5/8"-11"
12S2788-80	R	7"	2,200	3.4 1.5	3.9 99	11.7 297	5/8"-11"

** Governor controlled speeds

A tool for every abrasive application. Dotco...The Original.

Sanders

12L1820-05
Random Orbital
Sander



12L1850-09
Orbital Sander



3/16" Orbital

3/32"

3/16"

12L2384-B1
Belt Sander



Random Orbital & Orbital Sanders

These low profile random orbital and orbital sanders give the operator more sanding control and greater comfort. Available in 3/16" or 3/32" orbit pattern, Dotco sanders are lightweight with low vibration. Three interchangeable grips are shipped with each sander for greater comfort no matter what the hand size. 3/32" machines now have chrome levers so users can visually differentiate between 3/16" and 3/32" machines.

Belt Sanders—Dotco File

The new 12-23 Dotco file can grind corners, enter grooves or channels, debur, and strap polish. The unique belt cover makes belt changes quick and easy while accepting interchangeable arms for different application needs. Most important, there is also a high degree of interchangeable parts with other popular Dotco tools.

12-18 Series Random Orbital Sanders, 3/16" & 3/32" Orbit Patterns

Model No.		Sanding Pad Size	Free Speed rpm	Weight		Height		Length		
PSA	Hook & Loop			lbs.	kgs.	in.	mm	in.	mm	
12-18 Series - 0.24 hp (0.18kW) - 3/16" Random Orbital Sander - Non Vacuum										
	12L1820-03	12L1820-03HL	3.5"	12,000	1.56	0.71	3.33	84.58	5.11	129.79
	12L1820-05	12L1820-05HL	5.0"	12,000	1.62	0.73	3.33	84.58	5.48	139.19
	12L1820-06	12L1820-06HL	6.0"	12,000	1.68	0.76	3.33	84.58	5.48	139.19
12-18 Series - 0.24 hp (0.18kW) - 3/32" Random Orbital Sander - Non Vacuum										
	12L1823-05		5.0"	12,000	1.62	0.73	3.33	84.58	5.48	139.19
	12L1823-06		6.0"	12,000	1.68	0.76	3.33	84.58	5.48	139.19

12-18 Series Orbital Sander

Model No.	Abrasive Size	Speed orbits/minute	Weight		Height		Length		Width	
			lbs.	kgs.	in.	mm	in.	mm	in.	mm
12-18 Series - 0.24 hp (0.18kW) 3/16" Orbital Sander 10,000 OPM - Non Vacuum										
12L1850-09	3.66" x 9"	10,000	2.28	1.03	3.94	100.01	6.88	174.63	3.53	89.69

12-23 Series 0.5 Belt Sanders – Dotco File

Model No.	Contact Arm	Length		Width		Description	Power		Motor Speed		Belt Speed	
		in.	mm	in.	mm		hp	W	rpm	SFPM	SMPM	
12-23 Series - 0.5 hp (0.39kW) - Dotco File												
12L2384-B1	Straight	15	381	2.5	1.1	5/8" or 3/4"Wx18"L	.51	380	20,000	4,550	1,382	
12L2384-B2	Straight	15	381	2.5	1.1	1/2"Wx18"L	.51	380	20,000	4,550	1,382	
12L2384-B3	Offset	15	381	2.5	1.1	1/8", 1/4", 5/16", or 1/2"Wx18"L	.51	380	20,000	4,550	1,382	
12L2384-K1	Straight/Offset	15	381	2.5	1.1	Kit w/ 3/4", 1/2" & offset arms, belts & carrying case	.51	380	20,000	4,550	1,382	



AIRETOOL® • APEX®
 BUCKEY® • CLECO®
 COOPER AUTOMATION™
 DGD® • DOLER® • DOTCO®
 GARDNER-DENVER®
 GARDOTRANS™ • GETA™
 MASTER POWER®
 METRONIX™
 QUACKENBUSH™
 RECOULES™
 ROTOR™
 UTICA®

CooperTools
 P.O. Box 1410
 Lexington, SC 29071-1410
 Phone: (803) 359-1200
 Fax: (803) 359-2013
 www.dotco-tools.com