

FASTORQ® Lubricants



FASTORQ 444

FASTORQ 444 contains a 40% blend of lubricating solids, providing excellent protection from wear and grinding pressures of slow moving heavy machinery. This grease is primarily intended for use on open gears. It also works well as a heavy-duty thread compound, especially where resistance to water washout is important.

FASTORQ 444 offers the added advantage of long-term rust and corrosion protection. It is not only waterproof, but also contains additives specifically designed to prevent the damaging effects of salt and other corrosive elements.

FASTORQ 444 performs well in other applications that involve splines, u-joints, chucks, pillow block bearings and most high impact surfaces & heavily loaded, slow moving mechanisms. It can also be used in freezing temperatures, or in temperatures as high as 300° F.

NLGI Grade	4
Primary Functions	EP/anti-wear, corrosion protection
Appearance	Brown, slightly grainy
Solids Content	40%
Recommended Temp.	30°F - 300°F
Oil Description	Synthetic
Viscosity, SUS at 100°F	2000
Evaporation Rate	None
Solubility	Nil
Thickener	Inorganic

FASTORQ 444 is available in several container sizes:

Part Number	Container Size
FWP444-8	8 Lb, 1 Gallon Can
FWP444-40	40 Lb, 5 Gallon Pail
FWP444-128	128 Lb, 16 Gallon Keg