

# FASTORQ® Lubricants



## FASTORQ 70+

FASTORQ 70+ is a thread compound formulated to provide smooth make-up and breakout of threaded connections. Another primary function is the prevention of rust and corrosion.

FASTORQ 70+ contains well over 70% pure molybdenum disulfide, more than any other moly paste. For decades, moly has been recognized for its lubricity under pressure and its ability to pack solidly and smoothly into the pores of metal surfaces. It is also noted for its chemical stability at temperatures below 750°F. FASTORQ 70+ contains a significant concentration of rust and corrosion inhibitors, and also an H<sub>2</sub>S inhibitor.

FASTORQ 70+ is recommended for general use on threaded connections and press fits, and performs well as a lubricant for nut splitter chisels. It can also be used on seal rings and as a dressing for packing and o-rings. FASTORQ 70+ works well as a wear-in lubricant and also in a variety of other applications where sliding friction is present. It is recommended for use at temperatures not exceeding 750°F.

<b>Lubricant Classification</b>	Paste
<b>Appearance</b>	Smooth, dark gray
<b>Solids Description</b>	Pure molybdenum disulfide
<b>Solids Content</b>	Over 70% by weight
<b>Oxidation of Solids</b>	Begins at 750°F
<b>Oil Description</b>	Mixture of petroleum and synthetic oils
<b>Viscosity, SUS</b>	Not determined
<b>Evaporation Rate</b>	None
<b>Solubility</b>	Nil
<b>Binding Agent</b>	Complex Soap
<b>5% Salt Spray (ASTM B117)</b>	90 Days, Pass (No Rust)
<b>Humidity Cabinet (ASTM D1748)</b>	90 Days, Pass (No Rust)

FASTORQ 70+ is available in several container sizes:

Part Number	Container Size
FMP70-16BT	16 oz Brush Top Can
FMP70-16BT-C	16 oz Brush Top Cans, Case of 12
FMP70-2.25	2.25 Lb, 1 Pint Can
FMP70-2.25-C	2.25 Lb, 1 Pint Cans, Case of 12
FMP70-4.5	4.5 Lb, 1 Quart Can
FMP70-4.5-C	4.5 Lb, 1 Quart Cans, Case of 6
FMP70-18	18 Lb, 1 Gallon Can
FMP70-90	90 Lb, 5 Gallon Pail