

## FASTORQ RS18

FASTORQ RS18 is an excellent thread lubricant designed to eliminate wear and galling on stainless or other gall-susceptible threaded connections. FASTORQ RS18 does not reduce torque requirements to levels below those of other compounds. This is an important feature for applications involving rotary shouldered connections, or in other situations where over-torquing is a concern.

FASTORQ RS18 is also recommended for lubrication of shafts and other gall-susceptible mechanisms, which would normally be lubricated with smooth extreme pressure grease. It is intended for use at temperatures ranging from zero to 300° F. In addition, it is completely water-insoluble.

FASTORQ RS18 is a film forming lubricant. It has a strong polar attraction to metal surfaces and applies readily to threads and other machined parts. During use, a thin resilient coating is formed on areas subject to heavy loading and frictional heat. This thin layer helps prevent further abrasive contact between surfaces.

No stirring is needed prior to use.

<b>NLGI Grade</b>	2
<b>Primary Functions</b>	Extreme pressure / anti-galling
<b>Appearance</b>	Yellow, smooth
<b>Solids Content</b>	50%
<b>Recommended Temp.</b>	0°F - 300°F
<b>Oil Description</b>	Synthetic
<b>Viscosity, SUS at 100°F</b>	730
<b>Evaporation Rate</b>	None
<b>Solubility</b>	Nil
<b>Thickener</b>	Inorganic

FASTORQ RS18 is available in several container sizes:

<b>Part Number</b>	<b>Container Size</b>
RS18-12BT	12 oz Brush Top Can
RS18-12BT-C	12 oz Brush Top Cans – Case of 12
RS18-2.5	2.5 Lb, 1 Quart Can
RS18-2.5C	2.5 Lb, 1 Quart Cans – Case of 6
RS18-10	10 Lb, 1 Gallon Can
RS18-50	50 Lb, 5 Gallon Pail