03529351

# PISTON-TYPE AIR MOTORS REVERSIBLE

# SIZES 25HHWMC1 AND 35KKWMC1 BASE-MOUNTED and SIZES 25HHWM56C1 AND 35KKWM56C1 FLANGE-MOUNTED

#### LUBRICATION

WARNING: Lubricate the Motor before operating. To prevent leakage during shipment, all oil was drained from the Motor Case (1). Sufficient oil for one filling is contained in the can packed with the Motor. Before operating the Motor, check the Magnetic Drain Plug (2) at the bottom of the Motor Case and the Oil Level Plug (3) in the side of the Motor Case to make sure both are secure. Unscrew either Vent Cap (5) and pour entire contents of the can into the Motor Case.

Check the oil level daily.

When the Motor is not subjected to freezing temperatures: After the Motor has been idle for several hours or overnight, loosen the Magnetic Drain Plug (2) located at the bottom of the Motor Case (1) until the liquid in the Motor Case flows past Plug. Allow to drain until liquid changes from water to oil, then tighten the Plug. Remove the Oil Level Plug located on the side of the Motor Case, and one of the Vent Caps (5) and pour a sufficient quantity of the recommended oil through this opening to bring the oil level up to the open oil level hole. Replace Oil Level Plug and the Vent Cap.

When the Motor is subjected to freezing temperatures: Allow the Motor to remain idle long enough for the water content in the Motor Case (1) to separate from the oil, but not long enough for it to freeze. Drain the water and replenish the oil as above. Should this procedure be impractical, drain the entire contents from the Motor Case immediately after operation ceases, and pour the oil back into the Motor Case before resuming operation. If not drained, a sufficient quantity of water will eventually accumulate so that the Oil Splasher (12) attached to the Crank (11) will freeze fast.

For temperatures 30° to 80° F (-1.1 to 26.6° C), use Ingersoll-Rand Pneu-Lube® Medium Oil No. 50 or SAE 20 or 20W motor oil.

For temperatures above 80° F (26.6° C), use SAE 30 motor oil.

For temperatures below 30° F (-1.1° C), use SAE 10 or 20W motor oil. (Continued on Page 2.)

#### **HOW TO ORDER**

Order all repair parts for your Ingersoll-Rand Tool by the **NAME** and **NUMBER** shown in the Repair Part List Section. **Never** use the illustration numbers which appear in the first column.

For prompt service and genuine Ingersoll-Rand parts, place orders with the nearest Ingersoll-Rand Office or Authorized Distributor.

**Notice**: The use of other than genuine Ingersoll-Rand replacement parts may result in decreased tool performance and increased maintenance, and may, at the Company's option, invalidate all warranties.

FOR ADDITIONAL REPAIR SERVICE INFORMATION, REQUEST SERVICE BULLETIN \$6437.

Refer All Communications to the Nearest Ingersoll-Rand Office or Distributor.

© Ingersoll-Rand Company 1978

Printed in U.S.A.





Form P6437 Edition 1



Every three months, or as experience indicates, remove the Grease Plug (44) from the Base (42) and fill the chamber with Ingersoll-Rand Heavy Gear Grease No. 70.

Ingersoll-Rand Air Line Lubricators and Strainers are recommended for use with all Stationary Motors.

The No. SM450-A267AT Strainer and No. NL-32M Lubricator can be used in combination if a separate Strainer and Lubricator arrangement is desired. In selecting any other lubricator, strainer or filter arrangement make sure that its air passage capacity is sufficiently great to avoid restriction of compressed air to the Motor. For optimum performance, Sizes 25HHWMC1 and 25HHWM56C1 require 760 to 800 scfm at 90 psig (6.2 bar/620 kPa) while Sizes 35KKWMC1 and 35KKWM56C1 require 1000 to 1100 scfm.

#### **INSTALLATION**

A four-way valve is required because the reverse inlet is an auxiliary exhaust port when the Motor is operated in forward direction, and the forward inlet is the auxiliary exhaust port for reverse operation.

When selecting a valve, be sure to choose one that has an air passage capacity great enough to meet the demands of the Motors as defined in the foregoing paragraphs covering Strainers and Lubricators.

CAUTION: These Motors should be sufficiently loaded to prevent sustained speeds in excess of 1700 rpm for Size 25HHWMC1 or 25HHWM56C1; 1300 rpm for Size 35KKWMC1 or 35KKWM56C1. Higher speeds, except intermittently, will result in serious damage.

The Motor Case of a Stationary Motor can be rotated to any one of several different positions on the Base. When installation requires that the foot pad of the Base be attached to a wall or column so that it is not in a horizontal plane, the Motor Case must be removed from the Base and rotated. Position the Motor Case so that the Magnetic Drain Plug (2) is at, or not more than 20° from, the bottom vertical center.

Note: The bolt spacing of the Motor Case and Base is such that if the Motor is to be mounted in an inverted position with the foot pad at the top, or if the Motor is to be mounted on a wall or column so that the foot pad is vertical, a special Base must be used. Otherwise the Motor Case will be excessively tilted.

Caution: Stationary Motors should be mounted so that the axis of the Motor Shaft is horizontal. Operation of the Motor with the axis of the Shaft more than 10° from horizontal will result in lubrication difficulties.

#### Mounting Instructions for Series 56 Flange-Mounted Motors

These Motors can be mounted by either of two methods.

For Method No. 1, provide a mounting with a counterbore which is a close fit on the small diameter pilot on the Motor Mounting Cover (54) and with four mounting bolt holes that align with the four tapped holes in the Cover. Use mounting bolts that will enter no more than 1" (25.4 mm) into the tapped holes in the Cover.


For Method No. 2, provide a mounting with a counterbore which is a close fit on the large diameter pilot on the Motor Mounting Cover (54) and with a series of tapped holes that align with the bolt holes through the flanges on the Motor Case (1) and Motor Case Cover. Use the Motor Case Bolts (57) or replace these with longer ones if necessary, for attaching the motor assembly to the mounting.

Always provide a bearing for the outer end of the Motor Shaft. Locate it as far from the Motor as possible and be very careful to get good alignment.

Always provide an outboard bearing for pinions or shaft extensions. They cannot be overhung from the Motor Shaft.

Do not make shaft extensions a tight fit in the broached hole in the crank. An outboard bearing cannot be perfectly aligned with the crank bearings and the splined fit must act to a limited extent as a flexible coupling. Dimensions recommended for Motor Shaft splines will be furnished on receipt of mounting details and outboard bearing location. The Motor Shaft must be supported in such a manner that no end thrust will be transferred to the crank.

Size 35KKWMC1 Base-Mounted Motor



Flange-Mounted Motors Size 25HHWMC561 or 35KKWMC561

#### PARTS IN THE FOLLOWING LIST ARE USED ONLY IN BASE-MOUNTED MOTORS

PART NUMBER	FOR ORDERING
₩	•

		V	у
		25HHWMC1 25HHWM56C1	35KKWMC1 35KKWM56C1
1	Motor Case.	H5W-501	K5W-501
2	Magnetic Drain Plug	K5W-29	K5W-29
3	Oil Level Plug	D02-402	D02-402
4	Motor Case Eye Bolt (2)	KU-888	KU-888
*	Motor Nameplate	K5W-99	K5W-99
*	Nameplate Screw (6)	R4K-302	R4K-302
5	Vent Cap (2)	D02-302A	D02-302A
6	Vent Cap Cotter	D02-893	D02-893
7	Vent Cap Cotter  Vent Cap Chain	D02-891	D02-891
8	S-Hook	D02-421	D02-421
9	Vent Cap Screen	D02-421 D02-889	D02-421 D02-889
10		6CND-231-1/2	6CND-231-1/2
10	Vent Cap Screen Retainer	H5W-A516	K5W-A516
1.1	Crank Assembly	now-Ao10	K3W-A310
11	Bare Crank (consists of matched parts, none of which is sold	115117.51.6	TZ 5 W 7 1 Z
	separately)	H5W-516	K5W-516
12	Oil Splasher	HU-540	KU-540
13	Splasher Rivet, Long (2)	HU-541	K5W-541
*	Splasher Rivet, Short (2)	231-712	KU-542
14	Crank Lock Pin	HU-520	K5W-520
15	Lock Pin Nut	D02-394	D02-317
16	Lock Pin Cotter	D02-524	D02-330
*	Crank Pin Sleeve	HU-519	
17	Connecting Rod (5)	HH5D-509	K5M-509
18	Connecting Rod Bushing	HU-511	K5W-511
19	Crank Bearing (2)	HU-518	KU-518
20	Connecting Rod Ring (2)	HU-510	KU-510
21	Piston (5)	H5W-513	K5W-513
22	Piston Ring (one for each Piston)	HU-337	KU-337
23	Oil Regulating Ring (one for each Piston)	HU-338	KU-338
24	Wrist Pin (5)	H5W-514	K5W-514
25	Wrist Pin Retainer (10)	902A45-632	ILA902A9-589
26	Cylinder (5)	302A+3-032	K5W-505
*	Cylinder Head (5)	H5W-H505	
*		HH5D-L505A	
27	Cylinder Liner (5)	H5W-507	K5W-507
28	Cylinder Cap Screw (20)	D10-354	215-13
		HU-504	KU-504
29	Cylinder Cap Screw Washer (20)	HHWMC-545	KKWMC-545
30	Valve Chest		
31	1/4" Pipe Plug (2)	D02-402	D02-402
32	O-ring	11BMP-338	SM450B-607-1
33	Valve Chest Cover	H5W-546	K5W-546
34	Valve Chest Cover Gasket	H5W-928	K5W-928
35	Valve Chest Gasket	H5W-547	K5W-547
36	Valve Chest Screw (4)	12BMP-634	K5W-548
37	Lock Washer (4)	D02-321	D10-322
38	Rotary Valve	25HHWMC1-526	35KKWMC1-526
39	Valve Drive Pin	510-669A	510-669A
40	Valve Bearing	H5W-97	21-703
41	Motor Gasket	HH5D-592	K5W-592

<sup>\*</sup> Not illustrated.

## PARTS IN THE FOLLOWING LIST ARE USED ONLY IN BASE-MOUNTED MOTORS SIZES 25HHWMC1 AND 35KKWMC1

#### PART NUMBER FOR ORDERING

		<b>*</b>	*
		25HHWMC1	35KKWMC1
42	Base	H5M-292	K5W-292
43	Oil Seal	HM-270	KM-270
44	Grease Plug	D02-351	D02-351
45	Motor Shaft Bearing	E3G-763	D10-825
46	Bearing Spacer	HM-41	KM-41
47	Spacer Set Screw	C04-31	C04-31
48	Dust Washer	HM-298	KM-298A
49	Retaining Ring	HM-295	KM-295
50	Motor Shaft	HM-294	KM-294A
51	Shaft Key	E9G-758	D04-323
52	Motor Mounting Bolt (20)	215-148	215-36
53	Lock Washer (10)	D10-322	A-67

### PARTS IN THE FOLLOWING LIST ARE USED ONLY IN FLANGE-MOUNTED MOTORS SIZES 25HHWM56C1 AND 35KKWM56C1


#### PART NUMBER FOR ORDERING

		25HHWM56C1	35KKWM56C
54	Motor Mounting Cover	H5M-276	K5M-276
55	Dowel	D02-347	D02-347
56	Oil Seal	HM-271	KM-271
57	Motor Mounting Bolt (10)	215-37	KX36
*	Mounting Bolt Nut (10)	215-182	HU-776
*	Lock Washer (10)	D10-322	A-67
*	Motor Shaft (Blank, or finished to customer's specifications)	HM-277	KM-277

<sup>\*</sup> Not illustrated.

#### AIR STRAINER

ILLUS. NUMBER (Do not use for ordering)	PART NAME FOR ORDERING (Parts indented after an item are included with that item)	PART NUMBER FOR ORDERING
400	Air Strainer Assembly	SM450-A267AT
401	Air Strainer Screen	SM450-61AT
403	Air Strainer Plug	TA-464
404	Air Strainer Cap	SM450-268AT



#### **MAINTENANCE TOOLS**

TOOL NUMBER FOR ORDERING	TOOL NAME FOR ORDERING	OPERATION
HU-932 HU-933	Valve Chest Jack Bolt (2)	Removing the Valve Chest (30) from the Motor Case (1). Compressing the Piston Rings (22 and 23) when installing a Cylinder Liner (26) on Size 25HHWMC1 or 25HHWM56C1 Motor.
KU-933	Piston Ring Compressor	Compressing the Piston Rings (22 and 23) when installing a Cylinder (26) on Size 35KKWMC1 or 35KKWM56C1 Motor.

•Atlanta, Gs.
111 Ingersoll-Rand Drive
Chamblee, Georgia 30341

**★Baton Rouge, La.** 70816 4152 Rhoda Drive

★Birmingham, Ala. 35233 1516 Second Ave., South

\*Boston, Mass. 2 Kuniholm Dr. Holliston, Mass. 01746

\*Buffelo, N. Y. 14225 195 Sugg Rd. •Charlotte, N. C. 28208 4840 Wilmont Rd. \*Chattanooga, Tenn. 37407 1936 Central Ave.

Chicago, III.

888 Industrial Drive
Elmhurst, Illinois 60126

\*Cincineait, Ohio
666 Redna Terrace
Woodlown, Ohio 45215

\*Cleveland, Ohio 44125
9257 Midwest Ave.

\*Corpus Christi, Texas 78408
4540 Boldwin Blvd.

\*Dallas. Taxas 75247

●Dallas, Texas 75247 8901 Directors Row ★Denver, Colo. 80207 5805 E. 39th Ave.

Detroit, Mich.
 22122 Telegraph Road
 Southfield, Mich. 48075

Ingersoll-Rand®

Tool & Hoist Division 28 Kennedy Blvd. East Brunswick, N. J. 08816

★Freeport, Texas 77541 211 Park Place

●Hartford, Conn. 60 Progress Drive Manchester, Conn. 06040

●Houston, Texas 77001 6800 Sands Point, P.O. 1455

\*Indianapolis, Ind. 46268 5315 West 86th St.

●Los Angeles, Calif. 90022 5533 East Olympic Blvd.

•Milwaukee, Wis. N84 W13540 Leon Rd. Menomonee Falls, Wis. 53051

**★Minneapolis, Minn.** 55404 Corner Franklin & Cedar

\*Moline, III. 61265 3901 25 St.

\*Newark, N. J. 28 Kennedy Blvd. East Brunswick, N. J. 08816

•New Orleans, La. 70005 939 Lake Ave. Metairie

\*Peoria, III. 61614 1809 West Chanute Rd. Philadelphia, Pa.
 651 Park Ave.
 King of Prussia, Pa. 19406

ePittsburgh, Pa. 15220 6 Parkway Ctr.

\*Port Arthur, Texas 77640 5336 Twin City Highway \*Portland, Oregon 97214 240 S. E. Clay St.

★Richmond, Va. 23230 3431 West Leigh St.

\*San Francisco, Calif. 14299 Wicks Blvd. San Leandro, Calif. 94577

•Seattle, Wash. 98188 345 Andover Park East

\*Shreveport, La. 71106 450 W. 61st St.

**eSt. Louis, Mo. 63132** 1515 Page Industrial Blvd. \*Tampa, Fla. 33609 3316 South Westshore Blvd.

Washington, D. C. 20006 1666 K. St., N. W.

● Branch and All Star® Servicenter

★ All Star Servicenter only.

Calgary, Alberta, T2R 0E1 611 11th Ave., S. W.

Montreal, Quebec 620 Cathcart St., H3B 1M2 P.O. Box 1148, H3B 3K9

All Star Servicenter.

•Sherbrooke, Quebec, J1H 3X4 375 Courcelette St.

Sudbury, Ontario, P3A 3T3 P.O. Box 2220

#### CANADA

Canadian Ingersoll-Rand Co., Limited Montreal, Quebec 620 Cathcart St., H3B 1M2 P.O. Box 610, Station B H3B 3K3

Don Mills, Ontario M3B 2V1 255 Lesmill Road

Noncouver
 British Columbia, V6A 2W7
 1695 Main St.

Winnipeg, Manitoba, R3H 0M6 1234 Border St.

5-G7

#### **AUTONOMOUS COMPANIES**

Argentina, Buenos Aires

Ingersoll-Rand Argentina S.A.I.y C. Casilla Correo 2412, Correo Central

Australia, South Melbourne Ingersoll-Rand (Australia) Ltd. P.O. Box 219 42 Moray Street, 3205 Victoria

Austria A 1120, Vienna Ingersoll-Rand Ges M.B.H. Schoenbrunnerstrasse 213-215/2/5

Belgium, Diegem (Brussels) Ingersoll-Rand Benelux S.A. Kouterveldstraat 10-12, 1920 Diegem

Brazil, Sao Bernardo Ingersoll-Rand S.A. Ind. e Com. Caixa Postal 911

Chile, Santiago Ingersoll-Rand Chile Morande 341 Casilla 126-D

Colombia, Bogota Macquinarias Ingersoll-Rand de Colombia, S.A. Apartado Aero 7451

Denmark, Albertslund DK2620 Ingersoll-Rand AB Herstedvang 11

Egypt, Cairo Ingersoll-Rand North East Africa P.O. Box 820 23A Ismail Mohamed St. Zamalek

England, London, SW1X, 7LU Ingersoll-Rand Co., Ltd. Bowater House, Knightsbridge France, 78 190 Trappes Yvelines Compagnie Ingersoll-Rand Avenue Albert Einstein

Zone Industrielle Germany, 403 Ratingen Ingersoll-Rand GmbH Robt, Zapp Str. 7 Postfach 1380 Greece, Athens 610

Ingersoll-Rand Central Middle East 17th Floor Athens Tower

Mesogion-2-4
Hong Kong
Ingersoll-Rand Far East
19th Floor, Lap Heng House
50, Gloucester Road

India, Bombay 400018
Ingersoll-Rand (India) Private Ltd.
44 Maulana Abdul Gaffar Rd. P.O. Box 16564, Worli

Iran, Tehran Ingersoll-Rand Iran P.O. Box 12-1538

Ireland, Dublin Ingersoll-Rand Company (Ireland) Ltd. John F. Kennedy Drive

Italy, 20100 Milano Ingersoll-Rand Italiana, S.p.A. Strada Provinciale Cassanese Caselle Postale 1232 Vignate, Italy

Japan, 106 Tokyo Ingersoll-Rand (Japan) Ltd. Kowa Bldg. No. 17 2-7 Nishi-Azabu 1-Chome Minato-Ku

Kenya, Nairobi Ingersoll-Rand Mid Africa P.O. Box 14240

Malaysia, Petaling Jaya Ingersoll-Rand Malaysia, Sdn, Bhd. P.O. Box No. 125

Mexico, 10 D.F. Mexico Ingersoll-Rand S.A. de C.V. Apartado 41-666

Netherlands, Zoeterwoude Ingersoll-Rand Benelux N.V. P.O. Box 33, Zoeterwoude

Norway, Oslo 1 Ingersoll-Rand AB P.O. Box 143-Sentrum Peru, Lima

Ingersoll-Rand Co. of Peru, S.A. Casilla 2261

Philippines, Makati, Rizal 3117 Ingersoll-Rand Philippines, Inc. P.O. Box 445 MCC

Portugal, Lisbon 5 Ingersoll-Rand Lda Apartado 2933

Puerto Rico, San Juan 00936 Ingersoll-Rand de Puerto Rico Inc. G.P.O. Box 1222

Singapore 22 Ingersoll-Rand Southeast Asia (Pte.) Ltd. G.P.O. Box 2062, Singapore 1

South Africa, Alberton Ingersoll-Rand Co. S.A. (Proprietary) Ltd. P.O. Box 3720 Alrode, 1451

Spain, Madrid Cia. Ingersoll-Rand, S.A. Apartado 518

Sweden, Bromma Ingersoll-Rand A.B. S-16125 Bromma 1

Venezuela, Caracas Ingersoll-Rand de Venezuela S.A. Apartado 70588, Los Ruices

5-G7

#### AUTHORIZED I-R SALES AND SERVICE

Distributors in principal cities throughout the world. Contact the nearest Ingersoll-Rand office for the name and address of the distributor in your intry or write to Ingersoll-Rand International, Woodcliff Lake, New Jersey.