

- ⇒ **Spiral hose up to 30 ft trolley drive**  
Not for use in category II (Zone 1) or group IIC applications
- ⇒ **Energy supply by Square bar (even for curved beams)**  
consisting of: square track with tension arm, hose, hose holder, straining claw and rail carrier
- ⇒ **Energy supply by C-shaped rail**  
consisting of: C-rail with holder, adapter, antistatic supply hose and hose holder.  
The holder have to be clamped on the top flange of the I-beam.
- ⇒ **Lubricator**
- ⇒ **Filter silencer**
- ⇒ **Filter regulator**
- ⇒ **Grease cartridge for oil-free motor operation, 250 ml, Art. No. 11901**
- ⇒ **Booster Valve (from 30 ft Control length)**
- ⇒ **Pneumatic limit switch lifting and travelling**
- ⇒ **Extension arm for control on motor trolley**
- ⇒ **copper plated load hook for increased spark protection**  
(already included in additional charge for zone 1 as well as IIC)
- ⇒ **Stainless steel load hook (up to  $\frac{3}{4}$  ton carrying capacity)**
- ⇒ **Stainless steel chain (reduced carrying capacity) up to 6 Tl**
- ⇒ **Remote control (for cranes, hoists with trolleys)**
- ⇒ **Electropneumatic interface**
- ⇒ **Manual emergency lowering device for hoists 3-20 Tl or winches from LIFTER 1100**
- ⇒ **Hydraulic drives**
- ⇒ **Product training**
- ⇒ **Further accessories, available on request**

## Notice:

In the service section on our homepage under [www.jdneuhaus.com](http://www.jdneuhaus.com) you will find scaled drawings in 2D/3D format for download and linking in you CAD drawing.

