



# MICHIGAN PNEUMATIC TOOL

Industrial Air Tools

Heavy-Duty Industrial

# IMPACT WRENCHES

Serving All Industries

- Petro Chemical
- Construction
- Demolition
- Assembly
- Rental

1-800-521-8104 • [www.michiganpneumatic.com](http://www.michiganpneumatic.com)

# IMPACT WRENCHES

## MP-1632K-ST Multi-Function Ratchet Wrench Kit

Features a composite motor housing driving convertible 1/4" and 3/8" anvil for multi-purpose operation. Rear exhaust and a slim, compact head design make for a lightweight, yet powerful, solution for the job site.



Model	MP-1632K-ST
Square Drive	1/4" & 3/8"
Max Torque	30 ft-lbs
Free Speed	850 rpm
Length	6-1/8"
Weight	1.1 lbs
Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"
Avg. Air Consump.	4 cfm

## MP-2277A 3/8" Mini Impacting Ratchet

Features a unique design. A single jumbo hammer delivers one strong blow per revolution. This impacting ratchet drives the nut or bolt three times faster than the standard oscillating ratchet. Ideal for any mechanic or light assembly operation.



Model	MP-2277A
Square Drive	3/8"
Max Torque	55 ft-lbs
Free Speed	500 rpm
Length	6-1/8"
Weight	1.40 lbs
Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"
Avg. Air Consump.	4 cfm

## Impacting Ratchets

These ratchets feature a dual hammer pin impact mechanism designed to deliver a smooth blow to the ratchet yoke. Ideal for small engines and restricted work areas. Features a ball type anvil.

Model	MP-7131-ST	MP-7132-ST
Square Drive	3/8"	1/2"
Max Torque	90 ft-lbs	90 ft-lbs
Free Speed	600 rpm	600 rpm
Length	10-7/8"	11"
Weight	2.82 lbs	2.82 lbs
Air Inlet Thread	1/4"	1/4"
Rec'd Hose Size	3/8"	3/8"
Avg. Air Consump.	4 cfm	4 cfm



MP-7131-ST



MP-7132-ST

## MP-5287-H 1/4" Hex Drive Mini Impact Wrench

Featuring a super compact design. Twin hammer clutch mechanism provides durability and performance. Ideal for quick installation and removal of threaded fasteners. Excellent weight and balance to reduce operator fatigue. High torque output and a small size for demanding jobs in tight places.

Model	MP-5287-H
Square Drive	1/4"
Max Torque	94 ft-lbs
Free Speed	17,000 rpm
Length	4-5/16"
Weight	1.5 lbs
Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"
Avg. Air Consump.	12 cfm





# IMPACT WRENCHES

## MP-720-ST Straight Impact Wrench— 3/8" Square Drive

Features a friction ring anvil. This compact impact is easily maneuverable for hard to reach places, rugged and lightweight. The aluminum housing is protected by rubber guards. Equipped with swivel air inlet and built-in regulator. Butterfly trigger for better speed control.



Square Drive	Max Torque	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose	Avg. Air Cons.
3/8"	75 ft-lbs	10000 rpm	5-1/2"	2.25 lbs	1/4"	3/8"	3.0 cfm

## NPK

### NW-800S Straight Impact Wrench — 3/8" Square Drive

Features a pin-type anvil. Used mostly in repair shops, garages and assembly applications. Features include lightweight, low air consumption and exceptional power. Industrial model.



Square Drive	Max Torque	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose	Avg. Air Cons.
3/8"	48 ft-lbs	8000 rpm	7"	2.4 lbs	1/4"	1/4"	3.5 cfm

## NPK

### NAW-1200SPTS Straight Impact Wrench — 1/2" Square Drive

Features a pin-type anvil. Single hammer impact wrench is used in repair and garage work shops. Features a built-in power regulator to provide four steps of power control. This wrench is distinguished by its light weight, low air consumption and powerful impacting per blow. Uses brass end plates for longer wear. Industrial model.



Square Drive	Max Torque	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose	Avg. Air Cons.
1/2"	170 ft-lbs	7000 rpm	11"	4.3 lbs	1/4"	3/8"	3.5 cfm

### MP-1700 Pistol Impact Wrench — 1/2" Square Drive

Features a friction ring anvil. Twin Hammer clutch mechanism provides good durability and performance. Excellent weight and balance to reduce operator fatigue. High output motor provides high torque levels for removing nuts. **Model MP-1700P2 with a 2" extended anvil also available. Model MP-1700PA with pin-type anvil also available.**



Square Drive	Max Torque	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose	Avg. Air Cons.
1/2"	370 ft-lbs	6500 rpm	7"	5.3 lbs	1/4"	1/4"	23.8 cfm

# IMPACT WRENCHES

## NPK

### SW-12 3/8" Square Drive Angle Impact Wrench

Features a friction ring anvil. Used mostly in repair shops and garages. Features include lightweight, low air consumption and exceptionally powerful impacting per blow. Also features an integrated power regulator for easy adjustment. **Pin type anvil also available.**



Model	SW-12
Square Drive	3/8"
Max Torque	165 ft-lbs
Free Speed	8000 rpm
Length	4-7/8"
Weight	2.8 lbs
Air Inlet Thread	1/4"
Rec'd Hose Size	1/4"
Avg. Air Consump.	3.5 cfm

### MP-7775 1/2" Stubby Impact Wrench

Features a lightweight composite motor housing, a friction ring anvil and one hand forward/reverse. Ideal for use in repair shops & garages.



Model	MP-7775
Square Drive	1/2"
Max Torque	500 ft-lbs
Max Torque (Rev.)	940 ft-lbs
Free Speed	9000 rpm
Length	4-3/8"
Weight	2.50 lbs
Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"
Avg. Air Consump.	5.8 cfm

### MP-4311K-HT-KIT 1/2" Stubby Impact Wrench Kit

Featuring a super compact design. Aluminum housing and steel hammercase provides durability. Excellent weight and balance to reduce operator fatigue. High torque output and a small size for jobs in tight spaces. A must for auto, diesel and aircraft mechanics. **Kit includes case and sockets.**



Model	MP-4311K-HT-KIT
Square Drive	1/2"
Max Torque	400 ft-lbs
Free Speed	9000 rpm
Length	5"
Weight	3.00 lbs
Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"
Avg. Air Consump.	7-15 cfm



# IMPACT WRENCHES

## MP-2315-HE 1/2" Impact Wrench

Features a friction ring anvil. Twin hammer impact mechanism offers long, dependable service. A staple in any mechanics tool box. **MP-2315-HE-2 with 2" anvil also available.**

Model	MP-2315-HE
Square Drive	1/2"
Max Torque	680 ft-lbs
Free Speed	8000 rpm
Length	7-1/4"
Weight	5.8 lbs
Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"
Avg. Air Consump.	4.2 cfm



## MP-4314 1/2" Composite Impact Wrench

Features composite housing, push button forward reverse. One hand operation, aluminum hammer case and friction ring anvil. Ideal for mechanics in all industries.

Model	MP-4314
Square Drive	1/2"
Max Torque	820 ft-lbs
Free Speed	8000 rpm
Length	7-3/8"
Weight	4.21 lbs
Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"
Avg. Air Consump.	4 cfm



## Impact Wrenches

The MP-2660 is the most powerful weight to torque ratio 3/4" impact tool in our product line. This tool often replaces major brand name tools in the rental, heavy industrial and petro chemical applications. Outstanding cost to performance ratio as well to help you gain market share.

**Optional 6" anvil available. 3-Position Bail/Hanger (#2660-HGR) also available.**

Model	MP-2660	MP-2660-6
Square Drive	3/4"	3/4"
Max Torque	1100 ft-lbs	1100 ft-lbs
Free Speed	5500 rpm	5500 rpm
Length	9"	14-5/8"
Weight	9.50 lbs	10.5 lbs
Air Inlet Thread	3/8"	3/8"
Rec'd Hose Size	1/2"	1/2"
Avg. Air Consump.	14-38 cfm	14-38 cfm





# IMPACT WRENCHES

## MPT "Venom" Impact Wrenches

The latest addition to the MPT product line. Features include: lightweight composite handles, aluminum housings, twin hammers, sliding forward/reverse buttons, and an exhaust system that diverts exhaust down the handle for quiet operation and operator comfort. Ideal for rental, petro chemical and heavy industry applications.

**MP-2144QR-2 2" Extended Anvil also available.**

**MP-2144QR-P Pin Type Anvil also available.**

**MP-2146QR-6 6" Extended Anvil also available.**

**MP-2148QR-6 6" Extended Anvil also available.**



Model	MP-2144QR	MP-2146QR	MP-2148QR
Square Drive	1/2"	3/4"	1"
Max Torque	900 ft-lbs	1300 ft-lbs	1400 ft-lbs
Free Speed	8000 rpm	6000 rpm	6000 rpm
Length	7-3/4"	8-11/16"	8-7/8"
Weight	5.0 lbs	8.20 lbs	8.42 lbs
Air Inlet Thread	1/4"	3/8"	3/8"
Rec'd Hose Size	3/8"	1/2"	1/2"
Avg. Air Consump.	6.7 cfm	7.3 cfm	7.3 cfm





# RIGHT ANGLE IMPACT WRENCHES

## MP-1450RA Right Angle Impact Wrench — 1/2" Square Drive

Features a low profile angle head that allows access to the toughest bolt locations. Eliminates the need for awkward swivels and extensions. Offers the power of an impact wrench with the convenience of a ratchet.

**MP-1437RA 3/8" Square Drive also available.**

Model	MP-1450RA
Square Drive	1/2"
Max Torque	180 ft-lbs
Free Speed	7000 rpm
Length	13-3/8"
Weight	3.97 lbs
Air Inlet Thread	1/4"
Rec'd Hose Size	3/8"
Avg. Air Consump.	5 cfm



## NPK

### NAW-1200 1/2" Square Drive Right Angle Impact Wrench

Single hammer impact wrench is used in repair and garage work shops. Features a pin-type anvil and four steps of power control. This impact wrench is distinguished by its light weight, low air consumption and powerful impacts per blow. Uses brass end plates to increase durability.

### NAW-19A 3/4" Square Drive Right Angle Impact Wrench

Features a through-hole anvil. Right angle impact puts out the right amount of power for fast, effortless nutrunning of 3/4" nuts and bolts. Compact size and easy maneuverability permits nutrunning with minimum clearance. Built-in power regulator. Uses brass end plates to improve durability.

### NAW-32LA 1" Square Drive Right Angle Impact Wrench

Features a through-hole anvil. This 90° angle impact will perform with a gear assembly designed to bear heavy pounding. Used anywhere a straight type won't reach. Offers the ultimate in power for hard, big, tough nutrunning jobs in hard to reach areas with a minimum of clearance. Uses brass end plates for longer wear.



NAW-1200



NAW-19A



NAW-32LA

Model	NAW-1200	NAW-19A	NAW-32LA
Square Drive	1/2"	3/4"	1"
Max Torque	120 ft-lbs	470 ft-lbs	925 ft-lbs
Free Speed	7000 rpm	4000 rpm	3500 rpm
Angle Height	3-1/16"	5-13/16"	7-1/2"
Length	14-11/32"	16-3/8"	17-3/8"
Weight	6.6 lbs	23.3 lbs	39.6 lbs
Air Inlet Thread	1/4"	3/8"	1/2"
Rec'd Hose Size	3/8"	1/2"	1/2"
Avg. Air Consump.	3.5 cfm	17.7 cfm	30.0 cfm



# IMPACT WRENCHES

## Impact Wrenches

Features stainless steel throttle components, hammer case and cylinder. Bronze endplates for longer life. Ideal for high moisture and humidity regions. Ergonomic handle and trigger make it easy for the operator to maneuver and activate this impacting tool. Considered to be the most powerful 3/4" impact on the market today. Ideal for rental, petro chemical, and heavy industry. **Parts interchangeable with Ingersoll Rand IR-2925 series tool.**



750SS



751SS



#2080-A48  
Optional Dead Handle



#2910-A526  
Optional #4 Spline Anvil

Model	750SS	751SS	754SS
Square Drive	3/4"	1"	#4 Spline
Max Torque (Forward)	1800 ft-lbs	1800 ft-lbs	1800 ft-lbs
Max Torque (Reverse)	2000 ft-lbs	2000 ft-lbs	2000 ft-lbs
Free Speed	4600 rpm	4600 rpm	4600 rpm
Length	9"	9"	9"
Weight	13.5 lbs	13.5 lbs	13.5 lbs
Air Inlet Thread	3/8"	3/8"	3/8"
Rec'd Hose Size	1/2"	1/2"	1/2"
Avg. Air Consump.	58 cfm	58 cfm	58 cfm

## MP-796 1" Impact Wrench

Features a two jaw clutch for more power per pound, and a two piece motor housing for easy maintenance. Ideal for bridge and iron work and other confined spaces. **Optional #5 Spline also available.**



Model	MP-796
Square Drive	1"
Max Torque	2000 ft-lbs
Free Speed	4100 rpm
Length	9-1/2"
Weight	20 lbs
Air Inlet Thread	1/2"
Rec'd Hose Size	1/2"
Avg. Air Consump.	13 cfm



# IMPACT WRENCHES

## MP-2006 Pistol Impact Wrench — 3/4" Square Drive

Features a friction ring anvil. Twin hammer design built for power and durability. Well-balanced, comfortable grip handle and low noise combine to reduce operator fatigue. Features a three position power regulator built-in.

Model	MP-2006
Square Drive	3/4"
Max Torque	950 ft-lbs
Free Speed	5500 rpm
Length	8-1/2"
Weight	11.2 lbs
Air Inlet Thread	3/8"
Rec'd Hose Size	1/2"
Avg. Air Consump.	60 cfm



## MP-2920 Pistol Impact Wrench — 3/4" Square Drive

### MP-2920-1 Pistol Impact Wrench — 1" Square Drive

Features a twin hammer clutch for more power per pound, a pressure fed clutch lubrication system, two piece motor housing for easy maintenance, a built-in muffler for low noise and direct drive for fast run down.

Model	MP-2920	MP-2920-1
Square Drive	3/4"	1"
Max Torque	1100 ft-lbs	1100 ft-lbs
Free Speed	5500 rpm	5500 rpm
Length	12-1/2"	12-1/2"
Weight	12 lbs	12 lbs
Air Inlet Thread	3/8"	3/8"
Rec'd Hose Size	1/2"	1/2"
Avg. Air Consump.	38 cfm	38 cfm



MP-2920

## MP-6060 Pistol Impact Wrench — 3/4" Square Drive

### MP-6060-1 Pistol Impact Wrench — 1" Square Drive

### MP-6060-#4SPLINE Pistol Impact Wrench — #4 Spline Drive

Features a powerful two-jaw clutch and steel clutch housing design offers power and dependability. Model MP-6060-FR with a 3/4" friction ring anvil, Model MP-6060-1 with a 1" anvil and MP-6060-#4 spline anvil also available. Parts are interchangeable with CP-6060 series impact wrenches.

Model	MP-6060	MP-6060-1	MP-6060-#4SPLINE
Square Drive	3/4"	1"	#4 Spline
Max Torque	1100 ft-lbs	1100 ft-lbs	1100 ft-lbs
Free Speed	3000 rpm	3000 rpm	3000 rpm
Length	12-1/2"	12-1/2"	12-1/2"
Weight	12 lbs	12 lbs	12 lbs
Air Inlet Thread	3/8"	3/8"	3/8"
Rec'd Hose Size	1/2"	1/2"	1/2"
Avg. Air Consump.	38 cfm	38 cfm	38 cfm



MP-6060

# IMPACT WRENCHES

## MP-2740-ST 1" Impact Wrench

Features dual retainer anvil. Heavy-duty 1" impact allows fast rundown and high torque impact. Very effective in shipyards, bridge building, and heavy manufacturing plants.



Model	MP-2740-ST
Square Drive	1"
Max Torque	2500 ft-lbs
Free Speed	5000 rpm
Length	16-3/16"
Weight	22 lbs
Air Inlet Thread	1/2"
Rec'd Hose Size	1/2"
Avg. Air Consump.	10 cfm

## MP-3740L-ST 1" Impact Wrench

Features dual retainer anvil. Heavy-duty 8.3" extended anvil high torque impact is deal for use on wheels with recessed rims. Ergonomic angled handles for operator comfort.



Model	MP-3740L-ST
Square Drive	1"
Max Torque	1800 ft-lbs
Free Speed	6000 rpm
Length	19-3/8"
Weight	16.5 lbs
Air Inlet Thread	1/2"
Rec'd Hose Size	1/2"
Avg. Air Consump.	10 cfm



# HEAVY-DUTY IMPACT WRENCHES



MP-1034EITH



MP-1040EITH



MP-1550EITH

## Heavy-Duty Impact Wrenches

Features a twin hammer clutch for more power per pound, a pressure fed clutch lubrication system, two piece motor housing for easy maintenance and a built-in muffler for low noise and direct drive for fast run down. Parts are interchangeable with Ingersoll-Rand 2934, 2940 and 2950 series impact wrenches.

Model No.	Drive	Max Torque	Free Speed	Handle Trigger Type	Length	Weight	Air Inlet Thread	Rec'd Hose	Avg. Air Cons.
MP-1034EITH MP-1034EOTH MP-1034EI5S MP-1034EO5S	1" Sq. Thru-Hole 1" Sq. Thru-Hole #5 Spline #5 Spline	1100-1500 ft-lbs	6600 rpm	Inside Outside Inside Outside	11-1/4"	19 lbs	1/2"	3/4"	47 cfm
MP-1040EITH MP-1040EOTH MP-1040EI5S MP-1040EO5S	1" Sq. Thru-Hole 1" Sq. Thru-Hole #5 Spline #5 Spline	1600-2000 ft-lbs	5000 rpm	Inside Outside Inside Outside	12-13/32"	22 lbs	1/2"	3/4"	58 cfm
MP-1550EITH MP-1550EOTH MP-1550EI5S MP-1550EO5S	1-1/2" Sq. Thru-Hole 1-1/2" Sq. Thru-Hole #5 Spline #5 Spline	2500-3000 ft-lbs	3750 rpm	Inside Outside Inside Outside	14-1/2"	33 lbs	1/2"	3/4"	70 cfm



MP-1011EOTH



MP-1520EITH

## Heavy-Duty Impact Wrenches

Features a high energy per blow two jaw clutch, rugged steel clutch housing machined from bar stock, bronze alloy end plates for long motor life, a three piece housing for ease of maintenance and high power-to-weight ratio. Parts are interchangeable with Chicago Pneumatic 611 and 6120 series impact wrenches.

Model No.	Drive	Max Torque	Free Speed	Handle Trigger Type	Length	Weight	Air Inlet Thread	Rec'd Hose	Avg. Air Cons.
MP-1011EITH MP-1011EOTH MP-1011EI5S MP-1011EO5S	1" Sq. Thru-Hole 1" Sq. Thru-Hole #5 Spline #5 Spline	1800-2800 ft-lbs	6000 rpm	Inside Outside Inside Outside	12-1/2"	22.50 lbs	1/2"	3/4"	47 cfm
MP-1520EITH MP-1520EI5S	1-1/2" Sq. Thru-Hole #5 Spline	2500-3500 ft-lbs	3000 rpm	Inside	14-3/4"	33.75 lbs	1/2"	3/4"	60 cfm

# HEAVY-DUTY IMPACT WRENCHES

## NPK

### NWH-320P Pistol Impact Wrench — 1" Square Drive

Features a through-hole anvil. Industrial model. Efficient, heavy-duty clutch impact allows fast rundown and high torque output. Very effective in shipyards, bridge building, construction sites and heavy manufacturing plants.



Square Drive	Max Torque	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose	Avg. Air Cons.
1"	1300 ft-lbs	4000 rpm	10-13/16"	21.6 lbs	3/8"	1/2"	17.7 cfm

## NPK

### NW-32LA Impact Wrench — 1" Square Drive

Features a through-hole anvil. Straight type impact is ideal for extra heavy-duty jobs. Has terrific power for its weight. Will remove wheel nuts from big trucks and buses with ease. Uses brass end plates for longer wear.



Square Drive	Max Torque	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose	Avg. Air Cons.
1"	1000 ft-lbs	4000 rpm	15-1/16"	23.5 lbs	1/2"	1/2"	30.0 cfm

### MP-6100 Impact Wrench — 1" Square Drive

### MP-6100I Impact Wrench — 1" Square Drive, Inside Trigger

Features a through-hole anvil. Ideal for extra heavy-duty jobs, eliminating hand wrenches. Light, compact wrench for heavy assembly work.

Efficient, heavy duty clutch allows fast rundown and high torque output.

**Model MP-6100-5SPLN with spline drive or MP-6100G6 with 6" extended anvil available. Uses brass end plates for longer wear. Parts are interchangeable with CP-610 impact.**



MP-6100

Square Drive	Max Torque	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose	Avg. Air Cons.
1"	1440 ft-lbs	4000 rpm	14-1/2"	20.0 lbs	1/2"	1/2"	17.7 cfm

### MP-6100TA Torque Impact Wrench — 1" Square Drive

### MP-6100TA-5SPLN Torque Impact Wrench — #5 Spline Drive

Features a through-hole anvil. Torque controlled impact provides easy torque adjustment and uniform torque output. "Auto-Stop" feature tightens bolts to pre-specified tension. When preset torque is reached, tool stops automatically.

**Some MP-6100TA parts are interchangeable with the CP-610T impact.**



MP-6100TA

Square Drive	Max Torque	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose	Avg. Air Cons.
1"	1400 ft-lbs	4000 rpm	16-11/16"	23.5 lbs	1/2"	1/2"	17.7 cfm



# EXTRA HEAVY-DUTY IMPACT WRENCHES

## Extra Heavy-Duty Impact Wrenches

Feature, through-hole anvil, lever throttle, reinforced hangers, heat treated hammer, anvil and cams. Designed to produce an exceptionally high torque output. Effective for shipyards, bridge construction, building construction and heavy manufacturing plants. Time tested design for maximum durability.

Model No.	Drive	Max Torque	Free Speed	Length	Weight	Air Inlet Thread*	Rec'd Hose	Avg. Air Cons.
MP-5980	1-1/2" Sq. Through-Hole	10,000 ft-lbs	830 rpm	23"	88 lbs	3/4"	1"	138 cfm
MP-2588	2-1/2" Sq. Through-Hole	50,000 ft-lbs	355 rpm	26.63"	215 lbs	1"	1"	155 cfm
MP-3599	3-1/2" Sq. Through-Hole	80,000 ft-lbs	295 rpm	37.5"	600 lbs	1-1/4"	1-1/2"	375 cfm



*\*All Extra Heavy-Duty Impacts come with a live handle and dead handle*



*\*Ask your sales representative about our variety of sockets and other impact accessories*



MP-5980



MP-2588



MP-3599



# IMPACT WRENCH ACCESSORIES

## Replacement Parts

Michigan Pneumatic Tool has an unrivaled parts inventory that includes brand name, hard to find, obsolete, and discontinued parts. Over the years our engineers have identified common weaknesses in many popular tool designs, and have developed OEM level replacement parts that make the rebuilt tool perform and last longer than the original. We stock a comprehensive variety of parts, from the smallest washers to the largest housings, for all industrial air tools serviced by Michigan Pneumatic Tool. We have the parts you need, when you need them.



## Tune Up Kits Available for Most Industrial Models!

- IR-2920P (2920P-TK2)
- IR-2925P (2925-TK2)
- IR-2934 (2934-TK3)
- IR-2940 (2940-TK3)
- IR-3940 (3940-TK1)
- IR-3942 (3942-TK1)
- IR-2945 (2945-TK2)
- IR-2950 (2950-TK2)
- CP-6060 (C137568)
- CP-0611 (C115811)
- CP-0610 (C101089)
- CP-6120 (C101987)

Call for other models not listed

## Sockets

Michigan Pneumatic Tool has a wide variety of sockets available, please contact your sales representative for more information!





# SERVICE YOUR IMPACT WRENCHES

## WHAT WE DO

Michigan Pneumatic Tool is a full service air tool company celebrating 70 years as a leader in the design, distribution, manufacture, repair and rebuilding of industrial air tools. At MPT we service construction, industrial, demolition, bolting and foundry tools. Our service department is staffed by experienced technicians that are trained to rebuild any industrial grade air tool. We take pride in the ability to service virtually any make or model whether it is current or discontinued.

## HOW WE DO IT

Send your tool to MPT and experience the best service in the industry:

- ◆ An **estimate** is provided for repair within 3 business days of receiving your tool(s).
- ◆ Every tool is completely **disassembled**, cleaned and examined for wear and tear during the estimate process.
- ◆ Worn or damaged parts are **replaced** to reduce future maintenance costs or unnecessary tool replacement.
- ◆ Every tool is **tested** by our technicians then painted before it is returned to you.
- ◆ Note: When the cost to repair exceeds 50% of the cost of the tool, we will quote you a **replacement tool** as an option during the estimate process.
- ◆ Our tool repairs are completely **guaranteed**.
- ◆ Contact your sales representative for more information!





# MORE THAN JUST AN AIR TOOL COMPANY



Supplemental Tool Catalog



Material Removal



9500 Series Grinders




Chipping Hammer & Rivet Busters



Construction Air Tools



Rebuilt Pneumatic Tools Flyer



Winches & Material Handling



Compressed Air Pipe Systems



Pneumatic Tool Repair



HiVis Flyer



## MICHIGAN PNEUMATIC TOOL

### Industrial Air Tools

6850 Middlebelt Rd. • P.O. Box 906  
Romulus, MI 48174-7406

© 2017 Michigan Pneumatic® Tool, Inc.

