

*Products To Pull You Through The Tough Jobs*



## SLM Model Perfect Shop Hoist — H4 Duty Cycle Compact Design, Overload Protection

The Coffing model **SLM** Shop Hoist, featuring rugged construction and high H4 duty cycle, is the perfect hoist for around the shop or garage. This compact and job-proven hoist is ideal for commercial and industrial applications—lift up to 1000 pounds with 300 starts per hour. Put the **SLM** Shop Hoist to the test—it's *UP* for the task.

- H4 duty cycle (300 motor starts/hour).
- Easy installation and maintenance.
- Standard protector overload device.
- 10-pocket oblique lay liftwheel provides longer chain wear.
- Epoxy powder coat finish.
- 6½ ft. power cord with molded 3-prong plug on 115-volt units.
- NEMA 4 industrial-rated pendant control.
- Gear train—lifetime lubricated with non-oxidizing grease.
- Alloy load chain (zinc plated optional).
- Thermally protected hoist duty motor.
- D.C. braking system.
- Rugged cast aluminum alloy frame.
- 5:1 design factor.
- Small, compact design - commercial & industrial applications.
- Rigid hook suspension prevents tangling of power cord.
- Hardened forged steel, latch-style lower hook rotates 360°.
- True vertical lift.
- Totally enclosed, non-ventilated hoist frame protects motor from environmental contamination.
- Optional impact-resistant chain container available.
- Lifetime Warranty.
- Made in U.S.A.



**Model SLM**  
250-1000 Lbs.

*Made In USA*

*See Back — Specifications and Dimensional Drawing*

# DIMENSIONAL DRAWING

Model SLM

\* Dimension based on 10 ft. lift— will vary depending on actual lift

Reeving	A	B	C	D
single	11 <sup>1</sup> / <sub>16</sub>	3 <sup>7</sup> / <sub>8</sub>	2 <sup>15</sup> / <sub>16</sub>	3
double	12 <sup>1</sup> / <sub>8</sub>	5 <sup>3</sup> / <sub>4</sub>	2 <sup>3</sup> / <sub>8</sub>	3 <sup>9</sup> / <sub>16</sub>

All dimensions in inches

# SPECIFICATIONS

Model SLM 250-1000 Lbs.

Capacity (Lbs.)	Product Code				Lifting Speed F.P.M.	Reeving	Lift (Ft.)	Approx. Ship Wt. (Lbs.)
	**115-1-60	115-1-60	230-3-60	460-3-60				
250	15107W	—	—	—	16	single	10	26
250	—	15101W	15113W	15130W	16	single	10	28
250	—	—	15114W	15131W	24	single	10	28
250	—	—	15115W	15132W	40	single	10	28
300	15108W	—	—	—	16	single	10	26
300	—	15102W	15116W	15133W	16	single	10	28
300	—	—	15117W	15134W	24	single	10	28
300	—	—	15118W	15135W	40	single	10	28
500	15110W	—	—	—	8	double	10	32
500	—	15104W	15122W	15139W	8	double	10	34
500	15109W	—	—	—	12	single	10	26
500	—	15103W	15120W	15137W	12	single	10	28
500	—	—	15119W	15136W	16	single	10	28
500	—	—	15123W	15140W	20	double	10	34
500	—	—	15121W	15138W	24	single	10	28
600	15111W	—	—	—	8	double	10	34
600	—	15105W	15124W	15141W	8	double	10	34
600	—	—	15125W	15142W	12	double	10	34
600	—	—	15126W	15143W	20	double	10	34
1000	15112W	—	—	—	6	double	10	34
1000	—	15106W	15127W	15144W	6	double	10	34
1000	—	—	15128W	15145W	8	double	10	32
1000	—	—	15129W	15146W	12	double	10	32

\*\* Contactor in PB Station.

Products To Pull You Through The Tough Jobs

**⚠ WARNING**  
**Overloading and Improper Use Can Result In Injury**  
 To Avoid Injury:  
 • Do not exceed working load limit, load rating, or capacity.  
 • Do not use to lift people or loads over people.  
 • Use only alloy chain and attachments for overhead lifting.  
 • Read and follow all instructions.



Country Club Road • PO Box 779  
 Wadesboro, NC 28170 USA

Phone: (800) 477-5003 (704) 694-2156  
 FAX: (800) 374-6853 (704) 694-6829  
[www.coffinghoists.com](http://www.coffinghoists.com)