

## Fasteners To Tool Recommendation Chart

\*\*\*\*\* Tool recommended is the most cost effective solution \*\*\*\*\*  
 "." indicates the tool will install fastener but is not the most cost effective solution.  
 All tools will install a variety of fasteners. Refer to tool flyer for a complete list of fasteners that the tool will install.  
 "X" indicates the tool is not recommended for that fastener.

### Aerospace Blind Rivets

Tool	CHERRYMAX® HUCKMAX® ALLMAX® NAS9301 - 12	UNIMATIC® BLIND RIVET NAS1919S & U NAS1921S & U	UNIMATIC BLIND BOLT MAXIBOLT® MS21140/1 S & U MS90353/4 S & U	CHERRYLOCK® NAS1398/99 NAS1738/39	"A" CODE CHERRYLOCK "A" NAS1398A NAS1399A	NUTPLATE	GROUND STUD BACS53B1EA1/2	MBC® NAS1719 - 21	ASP® 2 ASP ASP FF ASP F ASP LC	UAB™ EN6122 & UAB130-EU EN6127 & UAB6127-EU EN6128 & UAB100-EU EN6129 & UABP-EU
GB51	1/8"	1/8"	X	X	3/32"-1/8"	3/32"-1/8"	X	1/8"	X	X
GB751	1/8" - 3/16"	5/32"-3/16"	5/32"	X	5/32"-3/16"	-	-8 & -10	5/32"-3/16"	13/64"	1/8"-5/32"
GB722	1/4"	1/4"	3/16"-1/4" ①	X	1/4"	-	-	-	21/64"	3/16"-1/4"
GBP745D	-	-	1/4"-5/16"	X	-	X	-	-	-	X
GB756	-	-	3/8"	-	-	-	-	-	-	-
GBP784B	X	X	X	1/8"-1/4"	X	X	X	X	X	X
*GBP2480	1/8"-1/4"	1/8"-1/4"	5/32"-1/4"	X	3/32"-1/4"	3/32"-1/8"	-8-10	3/32"	13/64"-21/64"	1/8"-1/4"
*GBP4801B	-	-	5/16"-3/8"	X	-	-	-	-	-	X
**GBP204	-	-	-	X	-	X	-	-	-	1/8"-1/4"
**GBP205	X	X	-	X	X	X	X	X	X	X
**GBP7XX	-	-	-	X	-	-	-	-	-	X
**GBP5XX	X	X	-	X	X	X	X	X	X	X

CHERRYMAX®, CHERRYLOCK®, MAXIBOLT® and MBC® are registered trademarks of Cherry Aerospace Fasteners. HUCKMAX®, ASP® and UNIMATIC® are registered trademarks of Alcoa Inc. ALLMAX® is a registered trademark of Allfast Fastening Systems, Inc. UAB™ is a trademark of Alcoa Inc.

①A-286 AND Ti ONLY  
 MOST TOOLS AVAILABLE WITH PISTOL GRIP (SH) AND IN-LINE SPLIT SYSTEMS (SR) AND/OR VACUUM COLLECTOR SYSTEMS.  
 GBP204 AND GBP205 HYDRAULIC INSTALLATION TOOLS ARE RECOMMENDED FOR OFFSET AND CLOSED ACCESS APPLICATIONS.

### Aerospace Lockbolts

Tool	LGPL Lightweight Groove Proportioned Lockbolt	GPL Groove Proportioned Lockbolt	MLGPL Metric Lightweight Groove Proportioned	MGPL Metric Groove Proportioned Lockbolt	NAS TENSION	NAS SHEAR
GB731	1/8"-1/4"	1/8"-1/4"	4mm-5mm	4mm-6mm	1/8"-1/4"	1/8"-1/4"
GBP745D	5/16"	1/4"-5/16"	6mm-8mm	6mm-8mm	1/4"-5/16"	1/4"-5/16"
GB756	5/16"-3/8"	5/16"-3/8"	8mm-10mm	8mm-10mm	5/16"-3/8"	5/16"-3/8"
*GBP2480	1/8"-1/4"	1/8"-1/4"	-	4mm-6mm	1/8"-1/4"	1/8"-1/4"
*GBP4801B	5/16"-3/8"	5/16"-3/8"	8mm-10mm	8mm-10mm	5/16"-3/8"	5/16"-3/8"
**GBP204	5/32"-1/4"	5/32"-1/4"	-4 & -6	-4 & -6	5/32"-1/4"	5/32"-1/4"
**GBP205	5/16"-3/8"	5/16"-3/8"	-	-	5/16"-3/8"	5/16"-3/8"

\*RECOMMENDED FOR HIGH PRODUCTION APPLICATIONS. GBP940 (ELECTRIC) OR GBP910C (AIR) POWERUNIT IS REQUIRED.  
 GBP204 AND GBP205 HYDRAULIC INSTALLATION TOOLS ARE RECOMMENDED FOR OFFSET AND CLOSED ACCESS APPLICATIONS.