

# Makita®

# 12V CORDLESS HAZARDOUS LOCATION DRIVERS

## HAZLOC™ CLASS 1 DIVISION 2 RATED



"Quick Change" 1/4" Hex Shank Chuck

Torque Adjusting System

Auto-Stop  
Fastening Function

L.E.D. Indicator

Built-in L.E.D. Light

Anti-Slip Dimpled Grip

Beeper Indicator

**MAKSTAR**  
CHARGING SYSTEM

Includes:  
2 Ea. (2.0Ah) Makstar®  
Battery BH1220,  
Makstar® Charger DC14SA  
& Steel Case



### CLASS I DIVISION 2 RATED

#### ADVANCED TECHNOLOGY



- UL listed for Class I Division 2 locations for maximum 50°C ambient
- Meets the NEC Article 513 Aircraft Hanger requirements for Class I Division 2 locations
- Tested to Mil Standard 810F, Method 511.4

### SMART SYSTEM

#### AUTO BATTERY SHUT-OFF



- Shuts-off the tool when battery capacity is less than 20%

#### Indication Lamp and Beeper

- Precision sensor indicates following conditions with light and/or beeping: sufficient fastening, insufficient fastening, low battery power, and battery too low to operate

### REPETITIVE ACCURACY

#### TORQUE ACCURACY



- Torque accuracy of: +/- 10% or +/- 3 sigma
- Automatically shuts-off tool when pre-set fastening torque is reached to ensure accuracy

### L.E.D. LIGHT SERIES

Models	BFH040SAE	BFH090SAE	BFH040FSAE	BFH090FSAE	BFH120FSAE
Fastening Torque: in. lbs. N·m	7 - 40 0.8 - 4.5	30 - 80 3.4 - 9.0	7 - 40 0.8 - 4.5	30 - 80 3.4 - 9.0	44 - 106 5.0 - 12.0
No Load Speed (RPM)	400	400	400	400	400
Class I Division 2 Approved	Yes	Yes	Yes	Yes	Yes
Torque Adjustment Grip	Yes	Yes	Yes	Yes	Yes
L.E.D. Light	No	No	Yes	Yes	Yes
L.E.D. Indicator	Yes	Yes	Yes	Yes	Yes
Beeper Indicator	No	No	Yes	Yes	Yes
Reverse Switch	Yes	Yes	Yes	Yes	Yes
Length (w/2.0Ah Ni-MH Battery)	7-15/32"	7-15/32"	7-15/32"	7-15/32"	7-15/32"
Height	10-15/32"	10-15/32"	10-15/32"	10-15/32"	10-15/32"
Width	2-13/16"	2-13/16"	2-13/16"	2-13/16"	2-13/16"
Weight (w/2.0Ah Ni-MH Battery)	3.3 lbs.	3.3 lbs.	3.3 lbs.	3.3 lbs.	3.3 lbs.

# CLASS I DIVISION 2 RATED