



**2.4
VOLT**

HEAVY-DUTY SCREWDRIVERS

SINGLE SPEED MODELS: 190 RPM

6539-6

• 3-PIECE BIT SET



6540-1 (KIT)

• 8-PIECE BIT SET



ADJUSTABLE
TWO POSITION
HANDLE

2-SPEED MODELS: 400/200 RPM

6546-6

• 3-PIECE BIT SET



6547-1 (KIT)

• 8-PIECE BIT SET



6547-22 (KIT)


• 1/4" CHUCK ATTACHMENT
WITH KEY

• 4-PIECE BIT SET



- 6-Position Adjustable Clutch
- Forward/ Reverse Button With Switch Lock Feature

ACCESSORIES



OFF-SET™ SCREWDRIVER POWER HEAD

48-32-2100 Use the power and speed of your 2.4 volt cordless screwdriver to fasten or remove screws, tight applications. Durable die cast construction. 1/4" magnetic bit reception for standard bits. 360° adjustable thumb flange. Maximum 100 in./lbs. torque 400 rpm.

48-32-2115 Cut Pack display case of 12, 48-32-2100.

8-PIECE 1/4" HEX DRIVE BIT SET

48-30-0101 Standard equipment for 6540-1 and 6547-1.



IMPACT RESISTANT CARRYING CASE ONLY

48-55-0798 Standard equipment for 6540-1, 6547-1 and 6547-22.

SPECIFICATIONS

MAXIMUM TORQUE (IN.-LBS.)

CATALOG NUMBER	VOLTS DC	SPEED RPM	DIAMETER	POSITION 1-2	POSITION 3-4	POSITION 4-5	POSITION 6	LENGTH (IN.)	NET WGT. (LBS.)	SHIP. WGT. (LBS.)
• 6538-1	2.4	190	1.4"	5 IN.-LBS.	12 IN.-LBS.	16 IN.-LBS.	22 IN.-LBS.	9	.88	1.0
6539-6	2.4	190	1.4"	5 IN.-LBS.	12 IN.-LBS.	16 IN.-LBS.	22 IN.-LBS.	9	.88	2.8
6540-1	2.4	190	1.4"	5 IN.-LBS.	12 IN.-LBS.	16 IN.-LBS.	22 IN.-LBS.	9	.88	4.9
• 6545-6	2.4	400/200	1.4"	3.5 IN.-LBS.	10.5 IN.-LBS.	17.5 IN.-LBS.	26 IN.-LBS.	9-3/8	.88	2.8
6546-6	2.4	400/200	1.4"	3.5 IN.-LBS.	10.5 IN.-LBS.	17.5 IN.-LBS.	26 IN.-LBS.	9-3/8	.88	2.8
6547-1	2.4	400/200	1.4"	3.5 IN.-LBS.	10.5 IN.-LBS.	17.5 IN.-LBS.	26 IN.-LBS.	9-3/8	.88	4.9
6547-22	2.4	400/200	1.4"	3.5 IN.-LBS.	10.5 IN.-LBS.	17.5 IN.-LBS.	26 IN.-LBS.	9-3/8	.88	5.2

STANDARD EQUIPMENT: **FOR 6538-1** • Single Speed Screwdriver. **FOR 6539-6** – 6538-1 Screwdriver, 48-30-1510 #1 Phillips Bit, 48-30-1520 #2 Phillips Bit, 48-30-0500 6-7 Slotted Bit, 2.4 Volt Battery Pack and 120 Volt AC One-Hour Battery Charger. **FOR 6540-1** – Same as 6539-6 Plus 1/4" Chuck Attachment with Key 49-22-1560, 8-Piece Driver/Drill Bit Set and Impact Resistant Carrying Case. **FOR 6545-6** • Two Speed Screwdriver. **FOR 6546-6** – Two Speed Screwdriver, 48-30-1510 #1 Phillips Bit, 48-30-1520 #2 Phillips Bit, 48-30-0500 6-7 Slotted Bit, 2.4 Volt Battery Pack, and 120 Volt AC One-Hour Battery Charger. **FOR 6547-1** – Same as 6546-6 Plus 1/4" Chuck Attachment with Key 49-22-1560, 8-Piece Driver/Drill Bit Set and Impact Resistant Carrying Case. **FOR 6547-22** – Two Speed Screwdriver, Two 48-11-0100 2.4 Volt Battery Packs, 48-59-0300 One-Hour Battery Charger, 1/4" Chuck Attachment with Key 49-22-1560, 48-32-2050 1/4" Nut Driver With 1/4" Hex, 48-89-0125 1/8" Twist Drill Bit, 48-89-0187 3/16" Twist Drill Bit, 48-89-0250 1/4" Twist Drill Bit and Impact Resistant Carrying Case.

• Unit Sold Less Battery Pack. Specifications Shown With Battery.

HEAVY-DUTY 2.4 VOLT CORDLESS TOOL ACCESSORIES



2.4 VOLT CORDLESS TOOLS	CAT. NO.	USE WITH TOOL MODEL NO'S
NI-CAD BATTERY	48-11-0100	6550-20, 6538-1, 6539-6, 6540-1,
1-HOUR CHARGER	48-59-0300	6545-6, 6546-6, 6547-1, 6547-22
VEHICLE CHARGER	48-59-0181	6545-6, 6546-6, 6547-1, 6547-22
IMPACT RESISTANT CARRYING CASE	48-55-0798	
CHUCK & KEY	49-22-1560	6546-6, 6547-1, 6547-22
KEY ONLY	48-66-3350	6546-6, 6547-1, 6547-22