



# HEAVY-DUTY STEEL TANK VACUUM CLEANERS



8911



8912



8925

- STAINLESS STEEL
- BOTTOM DRAIN VALVE FOR EASY WATER REMOVAL



- Wet/Dry Pickup Capabilities
- Positive Water Shut-Off  
On wet/dry machines protects motor from direct exposure to water.
- Heavy-Duty Filter System  
For the roughest coarse materials to the finest dust.
- Use As Blower  
Switch hose from intake to exhaust, for cleaning inaccessible areas.



8935



8950



VACUUM CLEANER DOLLY  
49-90-1150

For use with Model 8950 only.



8955



8965



## SPECIFICATIONS

CATALOG NUMBER	FOR MATERIALS	RECOV. CAP.		TANK	TANK DIMENSIONS	VOLTS	AMPS	MOTOR TYPE	MAX AIR FLOW CU. FT./MIN.	SEALED SUCTION IN WATER	OVERALL DIMENSIONS		NET WGT. LBS.	SHIP. WGT. LBS.
		GAL.	BU.								WIDTH	HEIGHT		
8911	WET/DRY	11	1-1/2	STEEL	16" DIA.	120	7.5	2-STAGE BYPASS	94	84"	22"	37"	56.0	66.0
8912	WET/DRY	11	1-1/2	STEEL	16" DIA.	120	9.2	3-STAGE BYPASS	92	134"	22"	37"	60.0	70.0
8925	WET/DRY	15	2	STAINLESS	16" DIA.	120	9.2	3-STAGE BYPASS	92	134"	22"	41"	63.0	74.0
8935	WET/DRY	6	3/4	STEEL	14" DIA.	120	7.0	2-STAGE BYPASS	94	84"	17"	28"	35.0	45.0
8950	WET/DRY	8	7/8	STEEL	14" DIA.	120 AC, 60 HZ	8.0	1-STAGE BYPASS	143	45"	16-3/4"	22-1/2"	18.0	25.0
8955	WET/DRY	10	1-1/8	STEEL	14" DIA.	120 AC, 60 HZ	8.0	1-STAGE BYPASS	143	45"	19-1/2"	38-1/2"	32.0	44.0
8965	WET/DRY	10	1-1/8	STEEL	14" DIA.	120	6.2	1-STAGE BYPASS	133	49"	19-1/2"	35-5/8"	34.0	45.0

**STANDARD EQUIPMENT:** All models are equipped with 1-1/2" O.D. hose connections, cord with 3-prong grounded plug, 3 hold-down clamps and 3 or 4-wheel caddy (except no. 8950) with non-marring wheels. **FOR 8911, 8912 and 8925** – Three paper filter bags, cloth filter, wire frame assembly, wet pick-up conversion pan, swivel connector and store-all tool bag. **FOR 8935** – Three paper filter bags, wet pick-up pan, cloth filter, wire frame assembly, swivel connector and wire hose carrier. **FOR 8950** – 1-1/2" O.D. hose connections, cord with 3-prong grounded plug, 3 hold-down clamps, 7' x 1-1/2" I.D. vinyl hose, hose adapter and filter cartridge. **FOR 8955** – 1-1/2" O.D. hose connections, cord with 3-prong grounded plug, 3 hold-down clamps, 7' x 1-1/2" I.D. vinyl hose, hose adapter, filter cartridge and 3 wheel dolly. **FOR 8965** – 7' x 1-1/2" I.D. vinyl hose, hose adapter, cloth filter assembly, foam filter sleeve, 3 wheel dolly and three paper filter bags.