



HEAVY-DUTY IMPACT WRENCHES

9078-22* (KIT)
• 3/4" SQUARE DRIVE WITH FRICTION RING AND THROUGH HOLE SOCKET RETENTION



325 FT.-LBS. MAX TORQUE
(3900 IN.-LBS.)

9079-22* (KIT)
• 1/2" SQUARE DRIVE



240 FT.-LBS. MAX TORQUE
(2880 IN.-LBS.)

9099-23* (KIT)
• 7/16" HEX QUICK-CHANGE
• VEHICLE CHARGER KIT INCLUDED



270 FT.-LBS. MAX TORQUE
(3240 IN.-LBS.)

* TOOL AVAILABLE WITHOUT BATTERY, CHARGER OR CASE. SEE "-20" MODEL IN SPECIFICATIONS CHART BELOW

THE MOST TORQUE OF ANY CORDLESS IMPACT WRENCH!

- Easily Removes And Tightens Lug Nuts On Vehicle Tires
- Handles Tough Equipment Applications
- 2.4 Amp-Hr NiCad Batteries Deliver Long Run Time
- Reversible Battery Pack Fits Into Cramped Work Spaces And Adjusts Balance
- One-Hour Universal Charger (Models 9079-23 and 9099-23 includes vehicle charger)
- Variable Speed Switch For Maximum User Control, 0-1400 RPM
- Reversing Lever With Trigger Lock-Off Prevents accidental activation when moving tool with a bit installed.
- Soft-Grip Handle Pad For operator comfort and secure grip.
- Mid-Handle Design For Comfort And Balance



EXCLUSIVE 9078-22 FEATURES:

- 325 Ft.-Lbs. Maximum Torque
- 3/4" Square Drive With Friction Ring And Through Hole Socket Retention

9079-22 AND 9079-23 FEATURES

- 240 Ft.-Lbs Maximum Torque
- 1/2" Square Drive Flat End Pin Detent Socket Retainer Holds Sockets And Adapters More Securely
- Quick Change Round Head Detent Pin Conversion Kit 49-17-0410 Is Included

9099-23 FEATURES

- 270 Ft.-Lbs. Maximum Torque
- 7/16" Hex Quick-Change Dual Ball Bit Ball Holder
- Hanger Bracket With Solid Steel Ring For hanging on belts, climbing pegs and/or for lifting with rope and clasp.

ACCESSORIES

5" LENGTH 1/2" SQUARE DRIVE EXTENSION

48-95-5000 Adapts to 1/2" Square Drive. Provides 5" additional length where required for use with sockets.

ROUND END DETENT PIN RETAINER KIT

49-17-0410 Can be substituted for the flat end pin detent style retainer for easier socket changes.

1/2" SQUARE DRIVE HEX SOCKETS



49-66-3080 1/2" 49-66-3110 11/16"
49-66-3090 9/16" 49-66-3120 3/4"
49-66-3100 5/8" 49-66-3130 13/16"

1/2" SQUARE DRIVE UNIVERSAL JOINT

48-03-0500 Fits 1/2" Square Drive and used with Hex Sockets to reach difficult places at various angles. Also allows clearance around obstructions.

1/2" SQUARE DRIVE TO 7/16" HEX ADAPTER

48-66-0061 Use with 7/16" hex shank auger bits, selffeed bits or other 7/16" hex shank accessories which have ball-retainer grooves.

SPECIFICATIONS

CATALOG NUMBER	VOLTS	MAX. TORQUE (FT.-LBS.)	MAX. TORQUE (IN.-LBS.)	RPM	IMPACTS PER MINUTE	LENGTH (INCHES)	NET WEIGHT (LBS.)	SHIP WEIGHT (LBS.)
• 9078-20	18	325	3900	0-1400	0-2200	11-3/4	6.8	7.5
9078-22	18	325	3900	0-1400	0-2200	11-3/4	9.2	18.0
• 9079-20	18	240	2880	0-1400	0-2200	11-3/4	6.6	7.3
9079-22	18	240	2880	0-1400	0-2200	11-3/4	9.0	17.8
9079-23	18	240	2880	0-1400	0-2200	11-3/4	9.0	17.8
• 9099-20	18	270	3240	0-1400	0-2200	12-1/4	7.1	8.0
9099-23	18	270	3240	0-1400	0-2200	12-1/4	7.1	18.5

STANDARD EQUIPMENT: FOR 9078-20 • - Tool Only. FOR 9078-22 - Includes Tool, Two 2.4 A-h Batteries, Universal Charger and Impact Resistant Carrying Case and Two Socket Retaining Rings. FOR 9079-20 • - Tool Only. FOR 9079-22 - Includes Tool, Two 2.4 A-h Batteries, Universal Charger and Impact Resistant Carrying Case. FOR 9079-23 - Includes Tool, Two 2.4 A-h Batteries, Vehicle Charger 48-59-0186, Round End Detent Pin, and Impact Resistant Carrying Case. FOR 9099-20 • - Tool Only. FOR 9099-23 - Includes Tool, Two 2.4 A-h Batteries, Vehicle Charger 48-59-0186 and Heavy Duty Contractor Bag.

• Tool only, less battery, charger and case.