



# HEAVY-DUTY SHARP-FIRE® SYSTEM SCREWS AND ACCESSORIES

## SYSTEM COMPONENTS

Power Unit (Included)	6702-20	Screw Guide Assembly	14-38-0685
Magazine Only (Included)	48-05-1000	Side Handle Assembly	14-34-0506
Extension Tube Assembly	14-38-0677		

**6706-20**  
0-2500 RPM  
1" - 2-1/4"



CATALOG #	LENGTH	DRIVE	BODY CORE HEAD TYPE	DIAMETER	THREAD	POINT	FINISH	PRIMARY APPLICATIONS
<b>Drywall Screws</b>								
48-30-3000	1-1/4"	#2 Phillips	Bugle	#6	Coarse	Sharp	Black Phosphate	Single layer of drywall to wood studs.
48-30-3005	1-5/8"	#2 Phillips	Bugle	#6	Coarse	Sharp	Black Phosphate	Double layer of drywall to wood studs.
48-30-3010	1-1/4"	#2 Phillips	Bugle	#6	Fine	Sharp	Black Phosphate	Single layer drywall to light gauge (20-25 gauge) steel studs.
48-30-3015	1-5/8"	#2 Phillips	Bugle	#6	Fine	Sharp	Black Phosphate	Double layer drywall to light gauge (20-25 gauge) steel studs.
48-30-3020	1-1/4"	#2 Phillips	Bugle	#6	Fine	Self-Drill	Clear Zinc	Single layer drywall to heavy gauge (12-20 gauge) steel studs.
48-30-3025	1-5/8"	#2 Phillips	Bugle	#6	Fine	Self-Drill	Clear Zinc	Double layer drywall to heavy gauge (12-20 gauge) steel studs.
<b>Underlayment Screws</b>								
48-30-3026	1-1/4"	#2 Phillips	Small Flat	#7	Hi-Lo	Sharp	Gray Phosphate	Underlayment to wood.
<b>Flooring Screws</b>								
48-30-3030	1-3/4"	#2 Square	Flat	#8	Coarse	Sharp	Yellow Zinc*	Subflooring.
48-30-3031	1-1/2"	#2 Square	Flat	#8	Double 14tpi	Piercing Point	Clear Zinc	Wood to steel - 3/4" plywood or OSB to 16 gauge steel.
48-30-3032	1-3/4"	#2 Square	Flat	#8	Coarse	Fluted-Point	Yellow Zinc*	High Density OSB (Advantec) or Particle Board to wood.
48-30-3033	2"	#2 Square	Flat	#8	Coarse	Piercing Point	Clear Zinc	Wood to steel - 1" to 1-1/2" wood to 16 gauge steel.
48-30-3035	2"	#2 Square	Flat	#8	Coarse	Sharp	Yellow Zinc*	Subflooring.
<b>Decking Screws</b>								
48-30-3040	2"	#2 Square	Flat	#8	Coarse	Sharp	Copperhead™**	Outdoor, treated lumber decks constructed with 5/4" top boards.
<b>Fiber Cement Screws</b>								
48-30-3050	1-1/4"	#2 Phillips	Modified Wafer	#8	Coarse	Self-Drill	Copperhead™	Fiber Cement Board to 16-20 gauge steel, rust resistant.
48-30-3051	1-5/8"	#2 Phillips	Modified Wafer	#8	Coarse	Self-Drill	Copperhead™	Fiber Cement Board to 16-20 gauge steel, rust resistant.
48-30-3052	1-1/4"	#2 Phillips	Modified Wafer	#8	Coarse	Sharp	Copperhead™	Fiber Cement Board to wood (ideal for tile backer).
48-30-3053	1-5/8"	#2 Phillips	Modified Wafer	#8	Coarse	Self-Drill	Clear Zinc	Fiber Cement Board to 16-20 gauge steel, not rust resistant

\*With Wax

## ACCESSORIES



### CARRYING CASE

48-55-0320 Standard equipment with 6708-21.

### SHARP-FIRE MAGAZINE ATTACHMENT

48-05-1000 Includes magazine, bit holder, square drive, phillips bit, wrenches and adaptor.

48-05-1005 Includes magazine, square drive bit, and phillips bit.



### #2 SQUARE DRIVE BIT

48-30-1526 120 mm used with 48-05-1000.  
48-30-1527 140 mm used with 48-05-1005.



### #2 PHILLIPS DRIVE BIT

48-30-1521 120 mm used with 48-05-1000.  
48-30-1528 140 mm used with 48-05-1005.



**3-WIRE 8' QUIK-LOK® CORD**  
48-76-4008 5-15P Standard with all models.

**3-WIRE 25' QUIK-LOK® CORD**  
48-76-4025 5-15P Optional.



**50 SCREWS PER STRIP.  
1,000 SCREWS PER BOX.**



### SCREW COATING DESCRIPTIONS

**Screw Coating**  
BP = Black Phosphate  
GP = Gray Phosphate  
CZ = Clear Zinc  
YZ = Yellow Zinc  
CH = Copper Head  
SS302 = 302 Stainless Steel

All flooring and decking screws are waxed for reduced torque and faster fastening.

### SCREW PACKAGING DESCRIPTIONS

1,000 Screws per Box  
Case Quantities Skid Quantities  
Screw Lengths under 2" (6 Boxes per case) .....40 Cases per Skid (240M screws per skid)  
Screw Lengths between 2" and 2-1/2"  
(6 Boxes per case) .....32 Cases per Skid (192M screws per skid)  
Screw Lengths 3" (6 Boxes per case) .....24 Cases per Skid (144M screws per skid)