




HEAVY-DUTY ADJUSTABLE CLUTCH SCREWDRIVERS

6580-20

- INCLUDES 1/4" NON-MAGNETIC BIT TIP HOLDER, #2 PHILLIPS BIT TIP, 6-7 3-1/2" SLOTTED BIT AND 10-12 3-1/2" SLOTTED BIT



**IMPROVED
ERGONOMICS,
SOFT-GRIP**



SUPERIOR COMFORT AND BALANCE

- Powerful 6.5 Amp Milwaukee Motor
 - Variable Speed Control
 - Lightweight Design—Only 3.6 Lbs
 - Avoid Stripped Screws With Controlled Torque
 - All Metal Gear Case and Diaphragm
 - Ergonomic Tactile Grip On Handle And Motor Housing
 - New Switch With Two-Finger Trigger
 - Quick Change Bit Retention Mechanism
 - Removable Belt Clip With Integral Bit Storage
 - Modular Brush Card Design
 - All Ball And Roller Bearings
 - 10' 2-Wire Quik-Lok® Cord
- Quick detachment from tool for tangle free carrying and storage. Instant field repair.



EXCLUSIVE 6580-20 FEATURES

- Multi-Position Torque Sensitive Clutch - 10 – 140 In.-Lbs.

EXCLUSIVE 6581-20 FEATURES

- Multi-Position Torque Sensitive Clutch - 10 – 110 In.-Lbs.

6581-20

- INCLUDES 5/16" MAGNETIC HEX SOCKET EXTENSION



**6.5 AMP
MOTOR**



SPECIFICATIONS

CATALOG NUMBER	VOLTS AC ONLY	AMPS	NO LOAD RPM	BIT SHANK SIZE	SPINDLE OFFSET	LENGTH	NET WGT.* LBS.	SHIP. WGT. LBS.
6580-20	120	6.5	0-1200	1/4" HEX	.92"	12-3/4	3.6	4.8
6581-20	120	6.5	0-2500	1/4" HEX	.92"	12-3/4	3.6	4.8

STANDARD EQUIPMENT 6580-20 – 48-32-3050 1/4" Bit Tip Holder, Non-Magnetic, 48-32-1050 #2 Phillips Bit Tip, 48-30-2601 6-7 3-1/2" Slotted Bit, 48-30-2651 10-12 3-1/2" Slotted Bit, 42-70-5280 Belt Clip, 48-76-5010 10' 2-wire Quik-Lok Cord. 6581-20 – 42-70-5280 Belt Clip, 48-76-5010 10' 2-wire Quik-Lok Cord, 49-66-3016 5/16" Hex Socket Extension.

* Weight Includes cord.