

- 0-980 RPM
- CHIPPING MODE EXCLUSIVE
- REMOVEABLE

**SDS BIT HOLDER** 



## **SPECIFICATIONS**

CATALOG NUMBER	VOLTS AC ONLY	AMPS	RPM	REMOVEABLE SDS BIT HOLDER	BLOW ENERGY (FTLBS.)	BLOWS PER MIN.	SOLID BIT CAPACITY	WOOD FLAT Boring Bit	STEEL TWIST DRILL	CORE BIT CAPACITY	LENGTH INCHES	NET WGT. LBS.	SHIP. WGT. LBS.
5362-6	120	6.8	0-900	NO	2.0	0-4500	1"	1-1/4"	1-1/2"	3-1/2"	14"	7.5	15.0
5359-21	120	7.4	0-980	NO	2.5	0-4200	1-1/8"	1-1/2"	1/2"	4"	13"	8.3	14.5
5360-21	120	7.4	0-980	YES	2.5	0-4200	1-1/8"	1-1/2"	1/2"	4"	13.3"	8.7	15.0

STANDARD EQUIPMENT: FOR 5359-21, 5360-21 AND 5362-6 – Depth Gauge, Side Handle and Impact Resistant Carrying Case.

## ACCESSORIES

