



HEAVY-DUTY 1-1/2" ROTARY HAMMERS

POWERFUL MOTOR! HARD HITTING! FAST DRILLING! • HIGHEST BLOW ENERGY, AMP RATING AND BPM IN THE 1-1/2" CLASS • LONG LIFE PNEUMATICS

- Powerful 11.0 Amp MILWAUKEE Motor
- Electronic Feedback Control Circuit (EFCC)
For reserve power (helps to maintain speed, won't bog down).
- "Soft-Shift" Stop-Rotation Mode Selector (5314-21 only)
- Two Operating Modes
Hammer with rotation and hammer only.
- Internal Clutch Slips If Bit Jams
- Sealed "AC Only" Switch
Keeps dust out, contacts clean.
- Excellent Power To Weight Ratio



5314-21



5314-21 FEATURES

- Single Motion Push-In SDS-Max Bit Reception
- SDS-Max Chisels Can Lock In 24 Multi-Positions

5318-21 FEATURE

- Single Motion Push-In Spline Bit Reception



5318-21



IMPACT RESISTANT CARRYING CASE

48-55-5315

SPECIFICATIONS

CATALOG NUMBER	VOLTS AC ONLY	AMPS	NO LOAD BLOWS PER MIN.	NO LOAD RPM	IMPACT ENERGY (FT-LBS.)	SOLID BIT CAPACITY	TUNNEL BIT CAPACITY	THICK WALL CORE BIT CAPACITY	THIN WALL CORE BIT CAPACITY	LENGTH	NET WGT. LBS.	SHIP. WGT. LBS.
5314-21	120	11.0	3400	385	7.9	1-1/2"	2-5/8"	4"	6"	17-1/2"	13.5	27.0
5318-21	120	11.0	3400	385	7.9	1-1/2"	2-5/8"	4"	6"	17-1/2"	13.5	27.0

STANDARD EQUIPMENT: For 5314-21: Tool, Side Handle and Impact Resistant Carrying Case. For 5318-21: Tool, Side Handle and Impact Resistant Carrying Case.