



HEAVY-DUTY POLY TANK VACUUM CLEANERS

WET/DRY PICKUP CAPABILITIES

8926



8927



8936-20



8938-20



8934-6

PRO-VAC



8926 AND 8927 FEATURES

- **Front Drain Valve With Hose Connector**
- **Polyethylene Tank**
High impact 1/4" wall construction. Resists rust and corrosive liquids.
- **Use As Blower**
Switch hose from intake to exhaust for cleaning inaccessible areas.
- **Heavy-Duty Filter System**
Large, totally enclosed filter bags provides larger filtration area and convenient disposal.

8926 EXCLUSIVE FEATURE

- **3-Stage Motor**
Produces 92 CFM, 134" waterlift.

8927 EXCLUSIVE FEATURES

- **Built-In Sensor Relay**
Activates vacuum when power is turned on. Preset time delay built-in to handle current spikes.
- **Three Position Switch**
On (Vacuum), Auto (Power/Tool Vacuum) and Off (Power/Tool Vacuum).
- **Built-In Power Outlet**
Accepts 3-prong plug.

8936-20 AND 8938-20 FEATURES

- **Easily Maneuverable**
- **High Efficiency Filtration System**
- **Durable Polypropylene Tank**
- **Handy Tool Caddy**
- **Ideal Applications**
Manufacturing Plants, Utility Plants, Schools, Construction Sites, Service Stations, Warehouses, Shopping Malls, Hotels and many more.

8936-20 EXCLUSIVE FEATURES

- **3-Position Switch—On/Off/On Demand**
- **Built-In Sensor Relay—Activates Vacuum When Power Is Turned On**
- **8.0 Amp Outlet Accepts 3-Prong Plug**
- **12.0 Amp Circuit Breaker**

8938-20 EXCLUSIVE FEATURES

- **Rear Drain Plug**
- **35' Cord Set**

8934-6 FEATURES

- **Lightweight – 5.0 lbs.**
- **High Impact Thermoplastic**
- **Built-In Rear Wheels**
- **Convenient Carrying Handle**
- **Large Disposable Paper Filter Bag**
- **18' Cord**
- **6.2 Amp Motor**

SPECIFICATIONS

CATALOG NUMBER	FOR MATERIALS	RECOV. GAL.	CAP. BU.	TANK	TANK DIMENSIONS	VOLTS	AMPS	MOTOR TYPE	MAX. AIR FLOW CU. FT./MIN.	SEALED SUCTION IN WATER	OVERALL DIMENSIONS WIDTH	HEIGHT	NET WGT. LBS.	SHIP. WGT. LBS.
8926	WET/DRY	21	2-1/4	POLY	16" DIA.	120	9.2	3-STAGE BYPASS	92	134"	21"	40"	62.0	82.0
8927	WET/DRY	21	2-1/4	POLY	16" DIA.	120	7.0	2-STAGE BYPASS	94	84"	21"	40"	56.0	76.0
8936-20	WET/DRY	7-1/2	7/8	POLY	14" DIA.	120	9.5	1-STAGE BYPASS	159	59"	14-5/8"	20-3/4"	17.0	20.0
8938-20	WET/DRY	9	1	POLY	15-1/2" DIA.	120	7.4	2-STAGE BYPASS	102	84"	16-1/8"	33-1/2"	34.0	37.0
8934-6	DRY ONLY	1-1/2 QTS.	–	THERMOPLASTIC	N/A	120	6.2	STRAIGHT THRU	80	–	6-1/4"	14-1/4"	5.0	7.0

STANDARD EQUIPMENT: FOR 8926 AND 8927 – Five Paper Filter Bags, Cloth Filter, Wire Frame Assembly, Wet Pick-Up Conversion Pan, Swivel Connector and Store-All Tool Pouch. FOR 8936-20 – 7' x 1-1/2" Hose, 1-1/2" Conversion Unit, Dolly Caster Assembly, Tool Basket, Cartridge Filter and Filter Bag. FOR 8938-20 – 7' x 1-1/2" Hose, 1-1/2" Conversion Unit, Vac Dolly, Tool Basket, Cartridge Filter and Filter Bag. FOR 8934-6 – 3' x 1-1/4" plastic hose, utility nozzle, crevice tool and mounting bracket.