



HEAVY-DUTY HEAT GUNS

8975-6

- DUAL TEMPERATURE
570° F AND 1000° F
- 3 POSITION ROCKER
SWITCH – OFF, HIGH & LOW



8980 (KIT)

- DUAL TEMPERATURE
570° F AND 1000° F
- 3 POSITION ROCKER
SWITCH – OFF, HIGH & LOW
- INCLUDES ACCESSORY
ASSORTMENT 49-80-0300



8977-20

- VARIABLE TEMPERATURE
140° F TO 1040° F
- ROTATE REAR HOUSING TO
SELECT TEMPERATURE



8985 (KIT)

- VARIABLE TEMPERATURE
140° F TO 1040° F
- ROTATE REAR HOUSING TO
SELECT TEMPERATURE
- INCLUDES ACCESSORY
ASSORTMENT 49-80-0300



- **Impact Resistant Heating Element**
- **Efficient Soft Air Velocity:**
Increases surface temperature to the required working temperature faster than conventional hot air heat guns. Maintains higher surface temperature, allowing faster completion standard commercial or industrial applications.
- **Cool Air Inlet Design**
Allows air movement at peak efficiency, even when resting on support stand.
- **Support Stand**
Enables gun to be stationary for workbench or assembly work, freeing both hands for use.
- **Users:**
Plumbers, Painters, Floor Covering Installers, Technicians, Boat Builders, Food Processing, Industry, Mechanics, Contractors, Body Shops, Photographers, Schools, Laboratories.
- **Applications:**
Softens, molds, bends and forms plastics. Pre-dries surfaces for fast preparation, softens caulking, putty and plastics, strips paint, varnish and lacquer. Repairs auto top vinyl, thaws frozen pipes, shrink fits plastic tubing, dries electric lines and cables, removes tiles, floor covering materials, loosens over-tightened screws and joints, welds plastics, PVC coated fabrics and foils.

SPECIFICATIONS

CATALOG NUMBER	VOLTS AC	AMPS	AIR VOLUME CU. FT. MIN.	AIR TEMPERATURES	LENGTH (IN.)	NET WGT. (LBS.)	SHP. WGT. (LBS.)
8975-6	120	11.6	14.8	570° F / 1000° F	10-1/8	1.6	2.0
8980 KIT	120	11.6	14.8	570° F / 1000° F	10-1/8	1.6	5.3
8977-20	120	11.6	14.8	140° F / 1040° F	10-1/8	1.6	2.0
8985 KIT	120	11.6	14.8	140° F / 1040° F	10-1/8	1.6	5.3

STANDARD EQUIPMENT: FOR 8975-6 – Dual Temp. Heat Gun. FOR 8980 – 8975-6 Heat Gun, Accessory Assortment 49-80-0300 and Impact Resistant Carrying Case. FOR 8977-20 – Variable Temp. Heat Gun. FOR 8985 – 8977-20 Heat Gun, Accessory Assortment 49-80-0300 and Impact Resistant Carrying Case.

ACCESSORIES

HIGH IMPACT CARRYING CASE

48-55-7120 Tough, custom molded rustproof, polyethylene case securely holds the 8975-6 and 8977-20 heat gun and all 4 accessory nozzles.



ACCESSORY ASSORTMENT

49-80-0300 Includes 49-80-0292, 49-80-0293, 49-80-0294 and 49-80-0297 to fit most common applications. Fits all heat guns offered by MILWAUKEE.

AIR REDUCTION

49-80-0297 Intensified heat in a specific area – soldering.

HOOK NOZZLE

49-80-0292 When heat is needed to surround-bending, soldering pipe, shrinking tubing.

DEFLECTOR

49-80-0293 Deflects air away from glass when stripping paint or softening putty.

AIR SPREADER

49-80-0294 Intensified heat for removing floor coverings, paint burning, vinyl top removal.