



HEAVY-DUTY PROFESSIONAL LEVER AND HAND CHAIN HOISTS

HAND CHAIN HOISTS
• 1/2 – 5 TON CAPACITY

- 9667-20
- 9668-20
- 9669-20
- 9670-20
- 9671-20
- 9672-20
- 9673-20
- 9674-20
- 9675-20
- 9676-20
- 9677-20
- 9678-20
- 9679-20
- 9680-20
- 9681-20



LEVER HOISTS
• 3/4 – 3 TON CAPACITY

- 9682-20
- 9683-20
- 9684-20
- 9685-20
- 9686-20
- 9687-20
- 9688-20
- 9689-20
- 9690-20
- 9691-20



9667-20 – 9681-20 FEATURES

- Hardened Load Chain For Flexibility And Long Wear
- Weston-Type Load Brake Requires No Lubrication
- Wheel Cover With Guide Slots Minimizes Jamming And Slipping
- Forged Swivel Hooks With Latches Reduces Twisting Of Chain And Unhooking Of Load When Chain Is Slack
- Standard Hand Chain Drop Is 2 Feet Less Than Lift
(Example: 8 foot lift hoist has 6 foot hand chain drop.)
- Simple, Efficient, Compact Design, Lightweight For Easy Installation, Even In Confined Spaces
- 1/2 – 5 Ton Capacity


9682-20 – 9691-20 FEATURES

- Weston-Type Automatic Braking System For Positive Load Control
- Forged Upper And Lower Hooks With Cast Steel Latches Standard
- Steel Chain Guide Roller And Chain Stripper For Smooth Chain Feed
- Double Reduction Dual Load Sharing Steel Gears
- Double Pawl Arrangement For Optimum Load Control
- Impact Resistant All-Steel Frame, Gear Case And Cover
- Minimal Maintenance With No Special Tools
- Hardened Link Type Alloy Steel Load Chain For Strength And Long Wear Life
- Free Wheeling Chain For Fast Load Attachment

SPECIFICATIONS

CATALOG NUMBER	RATED CAPACITY (TONS)	STANDARD LIFT (FT.)	CHAIN PULL TO LIFT RATED LOAD (LBS.)	FEET OF CHAIN OVERHAULED TO LIFT LOAD ONE FOOT (FT.)	SHIP. WGT. (LBS.)	CAPACITY					
						RATED CAPACITY (TONS)	1/2	1	2	3	5
9667-20	1/2	8	53	29	18.0	A HEADROOM	11-5/8"	13"	18-1/8"	21-29/32"	23-7/8"
9668-20	1/2	15	53	29	25.0	B WIDTH	4-15/16"	5-19/32"	8-5/16"	8-5/16"	8-5/16"
9669-20	1/2	20	53	29	30.0	C DEPTH	4-5/16"	5-1/16"	6-5/8"	6-5/8"	6-5/8"
9670-20	1	8	77	37	24.0	D DIAMETER	4-15/16"	5-19/32"	8-5/16"	8-5/16"	8-5/16"
9671-20	1	15	77	37	32.0	E HOOK OPENINGS	1-1/16"	1-1/32"	1-1/4"	1-5/16"	1-13/16"
9672-20	1	20	77	37	38.0						
9673-20	1	25	77	37	44.0						
9674-20	2	8	82	80	54.0						
9675-20	2	15	82	80	68.0						
9676-20	2	20	82	80	80.0						
9677-20	3	8	65	154	85.0						
9678-20	3	15	65	154	99.0						
9679-20	3	20	65	154	117.0						
9680-20	5	8	105	147	76.0						
9681-20	5	20	105	147	114.0						

CATALOG NUMBER	RATED CAPACITY (TONS)	STANDARD LIFT (FT.)	CHAIN PULL TO LIFT RATED LOAD (LBS.)	FEET OF CHAIN OVERHAULED TO LIFT LOAD ONE FOOT (FT.)	SHIP. WGT. (LBS.)	CAPACITY			
						RATED CAPACITY (TONS)	3/4	1-1/2	3
9682-20	3/4	5	33	-	19.0	A HEADROOM	12-5/8"	14-13/16"	18-11/16"
9683-20	3/4	10	33	-	21.0	B OUTSIDE CLEARANCE	2-3/16"	2-3/8"	4-3/16"
9684-20	3/4	20	33	-	26.0	C WIDTH	4-3/8"	4-3/4"	7-1/2"
9685-20	1-1/2	5	51	-	31.0	D OUTSIDE CLEARANCE	3-9/16"	3-15/16"	4-9/16"
9686-20	1-1/2	10	51	-	36.0	E OUTSIDE CLEARANCE	5-15/16"	6-7/8"	7-7/8"
9687-20	1-1/2	20	51	-	45.0	F LEVER LENGTH	11"	16-1/4"	16-1/4"
9688-20	1-1/2	25	51	-	51.0	G HOOK OPENING	1-1/8"	1-1/4"	1-9/16"
9689-20	3	5	77	-	51.0				
9690-20	3	10	77	-	59.0				
9691-20	3	20	77	-	72.0				



WARNING: MILWAUKEE lifting tools are not to be used for lifting, supporting or transporting people, nor for lifting loads over people.
 •MILWAUKEE does not cover freight and/or labor for inspection and testing of professional lifting tools (hoists) that are found not to be valid warranties.
 •Valid warranties must be substantiated by the discovery of defective material and/or workmanship.