



# HEAVY-DUTY 6-1/2" CIRCULAR SAWS

## 6310-22\*

• FOR WOOD CUTTING APPLICATIONS



EASY-TO-ADJUST  
BEVEL AND RIP  
FENCE KNOBS

RIGID AIRCRAFT  
ALUMINUM SHOE



## 6320-22\*

• FOR METAL CUTTING APPLICATIONS



DURABLE  
NICKEL  
PLATED  
STEEL SHOE  
To protect against  
scratching

PREMIUM BLADE FOR  
SMOOTH, BURR-FREE  
CUTTING.

CLEAR GUARD WINDOW FOR  
EXCELLENT LINE OF SIGHT



### ALL 18 VOLT CIRCULAR SAW FEATURES

- **One-Hour Universal Charger**  
Charger is compatible with slide-on style batteries.
- **18 Volt, 2.4 Amp-Hr Battery**  
Delivers more run time. Compatible with all other MILWAUKEE 18 volt products.
- **Electric Brake For Quick Blade Stops**
- **Powerful Milwaukee Built Motor With Replaceable brushes**
- **3200 RPM For Fast Cutting**
- **Ergonomic Cushion Grip D-Handle**  
Keeps hands in comfortable position at all cutting depths.
- **All-Metal Upper And Lower Guards**
- **Superior Balance**
- **Large, Easy Access, Lower Blade Guard Lever**
- **Left Blade Provides The Best Line Of Sight**

### 6310-22 CIRCULAR SAW FEATURES

- **Cuts More 2 X 4's Per Battery Charge Than Any Other Cordless Circular Saw**
- **Easily Cuts All 2X Material at 45° Bevel Angle**
- **Large 50° Bevel Capacity**

### 6320-22 METAL CUTTING CIRCULAR SAW FEATURES

- **Rugged Construction For Long, Trouble-Free Operation**
- **Spindle Lock And On-Board Hex Wrench For Easy Blade Change**
- **Common Materials Cut:**  
Conduit, Copper Pipe, Metal Studs, Unistrut And 'C' Channel, Plunge Cut And Fabricating Metal Duct Work, Angle Iron, Angle Steel, Black Pipe, Galvanized Pipe, Aluminum



\* TOOL AVAILABLE WITHOUT BATTERY, CHARGER OR CASE. SEE "-20" MODELS IN SPECIFICATIONS CHART BELOW

## SPECIFICATIONS

CATALOG NUMBER	VOLTS DC	NO. OF BATTERIES INCLUDED	BATTERY CAPACITY AMP-HRS	NO LOAD RPM	ARBOR SIZE	DEPTH OF CUT AT 90°	DEPTH OF CUT AT 45°	DEPTH OF CUT AT 50°	LENGTH W/O BATTERY	LENGTH W/ BATTERY	NET WGT. LBS. W/O BATT.	SHIP. WGT LBS.
• 6310-20	18	0	—	3200	5/8"	2-1/8"	1-9/16"	1-13/32"	12-3/4"	15-1/2"	6.6	8.1
6310-22	18	2	2.4	3200	5/8"	2-1/8"	1-9/16"	1-13/32"	12-3/4"	15-1/2"	6.6	26.9
• 6320-20	18	0	—	3200	5/8"	2-1/8"	—	—	11-1/4"	14"	6.4	8.5
6320-22	18	2	2.4	3200	5/8"	2-1/8"	—	—	11-1/4"	14"	6.4	20.5

**STANDARD EQUIPMENT: FOR 6310-20** • – Includes Circular Saw and 6-1/2" 24-Tooth Blade 48-40-4108 and Allen Wrench 49-96-0080. **FOR 6310-22** – Includes Circular Saw, Universal One-Hour Charger 48-59-0255, Two 18 Volt 2.4 Amp-Hr. Batteries, 6-1/2" 24-Tooth Blade 48-40-4108, Rip Fence Guide 49-22-1001, Allen Wrench 49-96-0080 and Impact Resistant Carrying Case. **FOR 6320-20:** Metal Saw 6320-20, Blade 48-40-4015 and Safety Glasses. **FOR 6320-22:** Metal Saw 6320-20, Blade 48-40-4015, Two Battery Packs 48-11-2230, Charger 48-59-0255, Safety Glasses and Contractor Bag 48-55-3510.

• Tool only, less battery, charger and case.