



# HEAVY-DUTY 3/4" SDS ROTARY HAMMER



5361-24\* (KIT)



- Drills Up To 54 Holes 1/4" x 1-1/2" Deep In Concrete On A Single Charge
- 18 Volt, 2.4 Amp-Hr Battery  
Delivers more time and is compatible with all other MILWAUKEE 18 volt products.
- One-Hour Universal Charger  
Compatible with ALL Power-Plus batteries.
- 1-3/4" Core Bit Capacity
- Powerful 18 Volt Rare Earth Motor Easily Handles All Drilling Applications
- Compatible With SDS, SDS-Plus And TE-C Style Bits
- Trigger Speed Control
- Two Mode Operation: Rotation With Hammer or Rotation Only
- Internal Clutch Protects Gearbox
- Lock-Off Switch
- Fully Adjustable Side Handle Rotates 360°
- Powerful Electro-Pneumatic Hammer Action
- Ball And Roller Bearings
- Depth Gauge For Drilling Holes To Preset Depth



\* TOOL AVAILABLE WITHOUT BATTERY, CHARGER OR CASE. SEE "-20" MODELS IN SPECIFICATIONS CHART BELOW

## SPECIFICATIONS

CATALOG NUMBER	VOLTS DC ONLY	NO. OF BATTERIES INCLUDED	BATTERY CAPACITY AMP-HRS	NO LOAD BLOWS PER MIN.	NO LOAD RPM	SOLID BIT CAPACITY	CORE BIT CAPACITY	LENGTH W/ BATTERY	NET WGT. LBS.	SHIP WGT. LBS.
5361-20	18	0	—	0-3900	0-850	3/4"	1-3/4"	17-1/2"	7.0	7.6
5361-24 KIT	18	1	2.4	0-3900	0-850	3/4"	1-3/4"	17-1/2"	9.5	17.7

STANDARD EQUIPMENT: FOR 5361-20 • 18 Volt Rotary Hammer, Side Handle and Depth Gauge. FOR 5361-24 – 18 Volt Rotary Hammer, 18 Volt 2.4 Amp-Hr Power-Plus Battery, Universal Charger, Side Handle, Depth Gauge and Impact Resistant Carrying Case.

• Tool only, less battery, charger and case.

## ACCESSORIES



### 5-PIECE 44 MAGNUM™ CARBIDE-TIPPED BIT SET

48-20-7490 Set includes one of each bit:  
 48-20-7410 (3/16"),  
 48-20-7431 (1/4"),  
 48-20-7441 (5/16"),  
 48-20-7451 (3/8"),  
 48-20-7471 (1/2").

### SDS/CHUCK ADAPTER KIT\*

48-66-1370 Kit includes chuck adapter No. 48-03-3005, 1/2" chuck No. 48-66-1360, chuck screw No. 06-75-3150 and chuck key No. 48-66-3280.



\* Parts in KIT may be ordered separately. Use part numbers listed above.