



HEAVY-DUTY CAULK & ADHESIVE GUNS

FOR AUTO GLASS INSTALLERS, ROOFERS, BUILDING CONTRACTORS, CABINET MAKERS, CARPET LAYERS AND OTHER CAULKING

6560-21*

- 10 OZ. SIZE
- HIGH FORCE



6560-23

- QUART SIZE
- MANUAL CLUTCH RELEASE FOR RAPID LOADING OF MATERIAL



6560-24

- 20 OZ. SIZE- "SAUSAGE FORMAT"



DRAMATICALLY REDUCES USER FATIGUE WHEN COMPARED TO MANUAL APPLICATION

6560-21, 6560-23 AND 6560-24 FEATURES:

- Long Run Time – Expels over 135 (10 oz.) Tubes of Latex Per Battery Charge
- Powerful – 620 lbs. of pushing force easily handles high viscosity materials such as windshield urethanes
- Interchangeable front-ends Works with: Standard caulk tubes, 29 oz. Sub-flooring adhesive, or sausage-packaged materials.
- All metal gear transmission Easily handles high pushing force and provides long life.
- Carriage Swivels 360° For easy caulking around corners and hard to reach areas.
- Ergonomic, T-handle design relieves stress to forearm
- Reversible Battery Pack– Exclusive to Milwaukee shifts weight and allows the operator to get into confined spaces
- Compact Size – 18.5" long w/ standard 10 oz. carriage
- Variable Speed Trigger - Allows for optimal bead control
- Auto Reverse Stops material from expelling when trigger is released, keeping work area clean.

* TOOL AVAILABLE WITHOUT BATTERY, CHARGER OR CASE. SEE "-20" MODELS IN SPECIFICATIONS CHART BELOW

SPECIFICATIONS

CATALOG NUMBER	VOLTS DC	SPEED: SEC. PER CARTRIDGE	CARRIAGE	LENGTH	NET WGT. (LBS.)	SHIP. WGT. (LBS.)
6550-20	2.4	46-120	—	17"	4.0	5.8
• 6560-20	12	—	NA	18-1/2"	2.9	3.5
6560-21	12	—	10 OZ.	18-1/2"	5.2	7.4
6560-23	12	—	QUART SIZE/30 OZ.	22-3/8"	6.2	8.2
6560-24	12	—	SAUSAGE PACK TYPE/20 OZ.	23-7/8"	5.7	7.8

STANDARD EQUIPMENT FOR 6550-20: Caulking Gun, 2.4 Volt Battery Pack and 2.4 Volt Battery Charger 48-59-0180. FOR 6560-20: 12V Caulk Gun only. FOR 6560-21: 12V Caulk Gun, 10oz. Carriage 48-08-1000, Plunger Rod 49-52-0500, Battery Pack 48-11-1967 and Universal Battery Charger 48-59-0255. FOR 6560-23: 12V Caulk Gun, Quart Size Carriage 48-08-1010, Plunger Rod 49-52-0525, Battery Pack 48-11-1967 and Universal Battery Charger 48-59-0255. FOR 6560-24: 12V Caulk Gun, 20oz. Sausage Style Carriage 48-08-1030, Plunger Rod 49-52-0515, Battery Pack 48-11-1967 and Universal Battery Charger 48-59-0255.

* Tool only, less battery, charger carriage and plunger rod.

ACCESSORIES (For "6560" series tools)


10 OZ. CARRIAGE

48-08-1000 Accepts all standard 10 oz. tubes/cartridges.



10 OZ. SAUSAGE STYLE BARREL

48-08-1020 Fits standard 10 oz. "sausage style" material packs.



PLUNGER RODS

49-52-0500 For use with 48-08-1000 10 oz. carriage and 48-08-1020 "sausage style" barrel.
49-52-0515 For use with 48-08-1030 20 oz. "sausage style" barrel.
49-52-0525 For use with 48-08-1010 quart size carriage.



QUART SIZE CARRIAGE

48-08-1010 Accepts quart size tubes/cartridges.



20 OZ. SAUSAGE STYLE BARREL

48-08-1030 Fits standard 20 oz. "sausage style" material packs.

