




# HEAVY-DUTY 1/2" MAGNUM® DRILLS

## 0234-6

• WITH KEYED CHUCK



## 0236-6 (KIT)

• INCLUDES 0234-6 MAGNUM® DRILL WITH STEEL CARRYING CASE AND REMOVABLE TRAY



## 0235-21

• 1/2" MAGNUM® DRILL WITH ALL-METAL, GRIP-LOK™, SINGLE SLEEVE CHUCK  
• INTERNAL SPINDLE LOCK-SINGLE HAND OPERATION TO TIGHTEN/LOOSEN CHUCK



ALL-METAL  
GRIP-LOK CHUCK  
2X GRIP  
STRENGTH  
ON BIT!



## 0244-1

• WITH KEYED CHUCK



- Powerful MILWAUKEE Built 5.5 AMP Motor
- Removable Brush Cartridge System  
Change brushes in less than one minute, with only a screw-driver. Self-stopping brushes. Includes spare brushes stored in cartridge.
- Aluminum Gear Case And Diaphragm Supplies Greater Support For Shaft And Bearings
- Heavy-Duty Industrial Chucks
- Trigger Speed Control Reversing Switches
- All Ball And Roller Bearings
- Helical Cut, Heat Treated Gears For Heavy-Duty Industrial/Construction Applications
- 8' 3-Wire Quik-Lok® Cord Sets  
Quick detachment from tool for tangle free carrying and storage. Instant field repair.



### EXCLUSIVE 0235-21 FEATURE

- All-Metal Grip-Lok™ Keyless Chucks  
For extreme durability. Carbide jaws for long life. High gripping torque prevents slippage. Lightly knurled for comfortable grip.

## SPECIFICATIONS

CATALOG NUMBER	CAPACITY IN STEEL	VOLTS AC ONLY	AMPS	NO LOAD RPM	GEAR TRAIN	SPINDLE DIAMETER AND THREAD	REPLACEMENT CHUCK CATALOG NO. CHUCK KEY INCLUDED	REPLACEMENT CHUCK KEY CATALOG NO.	LENGTH (IN.)	NET WGT. LBS.	SHIP. WGT. LBS.
0234-6	1/2"	120	5.5	0-850	DOUBLE	1/2" - 20	48-66-1360	48-66-3280	10-1/2	4.8	6.0
0235-21	1/2"	120	5.5	0-850	DOUBLE	1/2" - 20	48-66-1575	—	10-1/2	4.9	6.0
0236-6 KIT	1/2"	120	5.5	0-850	DOUBLE	1/2" - 20	48-66-1360	48-66-3280	10-1/2	4.8	14.8
0244-1	1/2"	120	5.5	0-600	DOUBLE	1/2" - 20	48-66-1360	48-66-3280	10-1/2	4.8	6.0

STANDARD EQUIPMENT: FOR 0234-6 – 8' 3-Wire Quik-Lok Cord 48-76-4008, Chuck, Chuck Key, Rubber Flex Key Holder 48-66-4040 and Side Handle 49-15-0260. FOR 0235-21 – 8' 3-wire Quik-Lok Cord 48-76-4008, Single Sleeve Keyless Chuck and Side Handle 49-15-0260. FOR 0236-6 – Variable Speed 1/2" Magnum Hole-Shooter No. 0234-1, 8' 3-Wire Quik-Lok Cord 48-76-4008, Chuck, Chuck Key, Rubber Flex Key Holder 48-66-4040, Side Handle 49-15-0260 and Steel Carrying Case 48-55-0711. FOR 0244-1 – 8' 3-Wire Quik-Lok Cord 48-76-4008, Chuck, Chuck Key, Rubber Flex Key Holder 48-66-4040 and Side Handle 49-15-0260.