



# HEAVY-DUTY 1/2" "D" HANDLE DRILLS & RIGHT ANGLE DRILLS

**ELECTRONICS** ON MODELS 1001-1, 1007-1, 1107-6, 1250-1, 3300-1, 3107-6 AND 3002-1

**1250-1**

• 0-1000 RPM

**1001-1**

• 0-600 RPM

**1101-1**

• 500 RPM



- 1/2" Trigger Speed Control Reversing
- 7.0 Amp MILWAUKEE Motors (All models except 3300-1.)
- Helical Cut, Heat Treated Gears
- Durable, Glass Reinforced Nylon Handles
- All Models Variable Speed, Control Reversing Except 1101-1 and 3102-6 (Single Speed Reversing)
- All Ball And Roller Bearings

**1007-1**

• 0-600 RPM

**1107-6**

• 0-500 RPM



**EXCLUSIVE 1007-1, 1107-6, 3107-6 AND 3300-1 FEATURE**

- 8' 3-Wire Quik-Lok® Cord Sets Quick detachment from tool for tangle free carrying and storage. Instant field repair.



**3102-6**

• PLUMBERS' KIT

**3002-1**

• ELECTRICIANS' KIT




**3107-6**

• VARIABLE SPEED KIT



## RIGHT ANGLE DRILL FEATURES

- Use With Up To 4-5/8" Selffeed Bits Model numbers 3107-6, and 3102-6 only.
- Steel Hardened Shafts
- Head And Handle Swivel 360° – Can Be Locked Tight In Any Position Allow 5-1/2" for right angle drill head and chuck.



**3300-1**

• MAGNUM® RIGHT ANGLE DRILL KIT



## SPECIFICATIONS

CATALOG NUMBER	CAPACITY IN STEEL	VOLTS AC ONLY	AMPS	NO LOAD DRILL ONLY RPM	NO LOAD RPM	INCLUDES DRILL NO.	GEAR REDUCTION	SPINDLE DIAMETER AND THREAD	RPM W/RAD LOW SIDE	HIGH SIDE	LENGTH (IN.)	NET WGT. LBS.	SHIP. WGT. LBS.
1001-1	1/2"	120	7.0	-	0-600	-	TRIPLE	1/2" - 20	-	-	14-3/4	6.8	7.5
1007-1	1/2"	120	7.0	-	0-600	-	TRIPLE	1/2" - 20	-	-	14-3/4	6.8	8.9
1101-1	1/2"	120	7.0	-	500	-	TRIPLE	1/2" - 20	-	-	14-3/4	6.8	8.2
1107-6	1/2"	120	7.0	-	0-500	-	TRIPLE	1/2" - 20	-	-	14-3/4	6.8	9.1
1250-1	1/2"	120	7.0	-	0-1000	-	DOUBLE	1/2" - 20	-	-	14-3/4	6.5	8.1
3002-1	1/2"	120	7.0	0-600	-	1001-1	QUADRUPLE	-	0-400	0-900	-	10.3	16.0
3102-6	1/2"	120	7.0	500	-	1101-1	QUADRUPLE	-	335	750	-	10.3	16.3
3107-6	1/2"	120	7.0	0-500	-	1107-6	QUADRUPLE	-	0-335	0-750	-	10.3	16.5
3300-1	1/2"	120	5.5	0-850	-	0234-6	TRIPLE	-	0-565	0-1275	-	8.0	16.9

**STANDARD EQUIPMENT: FOR 1250-1, 1001-1, 1101-1** – Side Handle, Chuck Key and Rubber Flex Key Holder. **FOR 1007-1 AND 1107-6** – Side Handle, 8' 3-Wire Quik-Lok® Cord Set 48-76-4008, Chuck Key and Rubber Flex Key Holder. **FOR 3102-6, 3002-1, 3107-6, 3300-1** – 48-06-2871 Right Angle Drive, 49-96-4060 9/16" Open End Wrench, 49-96-0080 3/16" Socket Wrench, Chuck Remover Bar, Side Handle and Impact Resistant Carrying Case 48-55-0802 (Steel Case for 3300-1 is 48-55-0200). **KITS 3300-1 AND 3107-6 ALSO CONTAIN:** 8' 3-Wire Quik-Lok® Cord Set 48-76-4008.