



# HEAVY-DUTY 15.0 AMP 7-1/4" CIRCULAR SAWS

**6375-20**



**6375-21 (KIT)**



**6376-20**

• **ELECTRIC BRAKE**



- **15.0 Amp, 3-1/4 Max HP Milwaukee-Built Motor**  
Easily cuts through tough materials including header, microlams and wet lumber without stalling.
- **Constant Handle Position**  
Vertical depth adjustment system keeps handle position intact for comfortable operation.
- **Fast, Smooth Adjustments**  
Reinforced vertical bracket provides smooth depth adjustment. Oversized knob and lever provides quick, positive locking.
- **Easy-To-Read Scales**  
Cast in rip scale in front of shoe measures blade to edge of shoe on both sides for accurate ripping.
- **50 Degree Bevel Capacity**  
Extra bevel capacity to cut joists, rafters and trusses for unique roof angles.
- **Extra Wide, Lightweight Shoe**  
Extra wide, magnesium shoe provides maximum stability and allows use of clamped saw guide (speed square) without motor interference.
- **Perfect Balance**  
Center balanced, saw remains level when balanced with one finger against trigger.
- **Milwaukee Durability**  
Hardened steel helical gearing, 100% sealed ball bearings, impact resistant glass reinforced nylon motor housing, magnesium shoe, durable, flexible rubber cord set.



- **FAST, SMOOTH ADJUSTMENTS**  
Reinforced vertical bracket provides smooth depth adjustments. Oversize knob and lever provides positive locking. Positioned to maximize line of sight when cutting.



- **ON-BOARD WRENCH**  
Built-in wrench storage on shoe speeds blade changes, eliminates lost, misplaced blade wrenches.



- **50° BEVEL CAPACITY,**  
Ideal for roof rafters, trusses and joists.

## SPECIFICATIONS

CATALOG NUMBER	BLADE SIZE	VOLTS	AMPS	NO LOAD SPEED RPM	ARBOR	DEPTH OF CUT AT 90°	DEPTH OF CUT AT 50°	DEPTH OF CUT AT 45°	NET WEIGHT LBS.	SHIP. WEIGHT LBS.
6375-20	7-1/4"	120 AC-DC	15.0	5800	5/8"	2-5/16"	1-5/8"	1-13/16"	11.5	16.5
6375-21	7-1/4"	120 AC-DC	15.0	5800	5/8"	2-5/16"	1-5/8"	1-13/16"	19.5	24.5
6376-20	7-1/4"	120 AC ONLY	15.0	5800	5/8"	2-5/16"	1-5/8"	1-13/16"	11.5	16.5

**STANDARD EQUIPMENT:** FOR 6375-20 – 7-1/4" Circular Saw and Carbide Blade. FOR 6375-21 – 7-1/4" Circular Saw, Carbide Blade, Rip Fence and Impact Resistant Carrying Case. FOR 6376-20 – 7-1/4" Circular Saw With Electric Brake and Carbide Blade.

## ACCESSORIES




**IMPACT RESISTANT CARRYING CASE**  
48-55-9166 Standard equipment with 6375-21.

**RIP FENCE KIT**  
49-22-4146 Includes two thumb screws.

**RIP GUIDE KIT**  
49-22-4160 Includes one thumb screw.

**BLADE WRENCH**  
49-96-6205



**ENDURANCE® BLADES**  
Extra long life, construction and finishing blades. Carbide C3 grade micro ground teeth stay super sharp.



**"Y" GREASE 1 LB. CAN (OR) 6 OZ. TUBE**  
49-08-5275 (Can) 49-08-5270 (Tube)