



HEAVY-DUTY ELECTROMAGNETIC DRILL PRESSES

4204-1

- INCLUDES 4253-1
MOTOR AND
4203 BASE



4206-1

- INCLUDES 4262-1
MOTOR AND
4203 BASE



MOTOR AND STAND COMBINATIONS 120 VOLT AC ONLY

- Base Control Panel Includes Variable Speed Adjusting For Motor
- Solid State Electronic Switching
- Feedback Speed Control
- Computer Controlled Reverse
- Full Wave Magnetic Holding Power
- Forward/Reverse Control
- Superior Cutting Tool Performance
- Line Lock-Out
Prevents tool from operating should voltage be restored to an interrupted line when switch is locked in the "on" position.
- Motor/Magnet Interlock
- Automatic Base/Chip De-Mag
- Automatic Electronic Soft Start
- For Use On Any Flat Ferrous Material 1/2" And Thicker

ACCESSORIES

STEEL HAWG® METAL CUTTERS

See page 129.



ARBORS

See page 130.



SPECIFICATIONS

| CATALOG NUMBER | VOLTS AC ONLY | AMPS | CAPACITY | | *DRILL POINT PRESSURE LBS. | REPLACEMENT CHUCK CATALOG NUMBER | REPLACEMENT CHUCK KEY CATALOG NUMBER | WEIGHT LBS. |
|----------------|---------------|------|----------|---------|----------------------------|----------------------------------|--------------------------------------|-------------|
| | | | DRILL | TAP | | | | |
| 4204-1 | 120 | 7.2 | 1/2" | 5/8"-18 | 1650 | 48-66-1360 | 48-66-3280 | 57 |
| 4206-1 | 120 | 12.5 | 3/4" | 1"-14 | 1670 | 48-66-2085 | 48-66-3160 | 70 |

* Drill point pressure on a 1" thick steel plate with the chuck mounted closest to the base. Values for numbers 4204-1 and 4206-1 are with the base adjusted to the rearward position.