

HEAVY-DUTY 7"/9" 13.0 AMP SANDERS

- MILWAUKEE Sanders May Be Converted To Grinders By Using The Proper Wheel Guard For Grinding Operations.
- Powerful 13.0 Amp 2-1/4 Maximum HP With Long Life Brushes And High Output Fans Provides high performance power for grinding, cutting, and finishing operations.
- Optimum Speed Range For Various Accessories Including resin bonded abrasives, wire brushes, resin fiber discs and abrasive flap discs.
- All Ball And Roller Bearing Construction
 Spiral Bevel Gears
 For optimum motor torque transfer, improved performance and durability. Replaceable armature pinion gear.
- Cast Aluminum Gear Housing With Recessed Spindle Lock Accessory change is fast and easy – single wrench operation.
- 2-Position Side Handle
- Adjustable Wheel Guard
- Lock-On Button For Continuous Operation

EXCLUSIVE 6078 FEATURE:

- **Dial Speed Control** To match optimum RPM to application.
- 2-Wire Quik-Lok[®] Cord^{*} Sets Quick detachment from tool for tangle free carrying and storage. Instant field repair and safe replacement. Tools come with 2-wire, 10'-16 gauge rubber cord No. 48-76-5010. A 25' cord No. 48-76-5025 is also available.



*2-Wire Quik-Lok Cord is not compatible with previous 3-Wire Quik-Lok configurations.

SPECIFICATIONS

CATALOG NUMBER	SPEED RPM	DISC DIA.	VOLTS	AMPS	MAX. POWER OUTPUT (WATTS)	MAXIMUM HORSEPOWER	SPINDLE THREAD SIZE	LENGTH	NET WGT. LBS.	SHIP. WGT. LBS.
6072	5000	7"/9"	120 AC-DC	13.0	1680	2-1/4	5/8"-11	17"	9.3	11.3
6078	0-6000	7"/9"	120 AC ONLY	13.0	1680	2-1/4	5/8"-11	17"	9.3	11.3

STANDARD EQUIPMENT: FOR 6072 — Side Handle, Flange and Nylon Washer Only. Order All Accessories Separately. FOR 6078 — Side Handle, 10' 2-Wire Quik-Lok Cord, Flange and Nylon Washer Only. Order All Accessories Separately.

ACCESSORIES

STEEL CARRYING CASE

48-55-0890 For all 13.0 and 15.0 amp Grinders and Sanders. 6080-20, 6081-20, 6082-20,6086-20, 6088-20 & 6089-20 sander/grinders will only fit if the wheel & guard are removed.

TYPE "G" GREASE

49-08-4140 1 lb. can





