



HEAVY-DUTY 15.0 AMP SANDERS

6080-20

- 7"/9" DIAMETER
- 6000 RPM



**SUPERIOR
ERGONOMICS**



6081-20

- 7"/9" DIAMETER
- 6000 RPM



**OUTSTANDING
DURABILITY AND
PERFORMANCE**



6082-20

- 7"/9" DIAMETER
- 6000 RPM
- EXCLUSIVE 9-POSITION ROTATING MAIN GRIP



- **Powerful 15.0 Amp 4.0 Maximum Horsepower**
Provides high performance power for grinding, cutting, and finishing operations.
- **Side And Main Grip Angled For Optimum Comfort**
- **Lightweight**
- **Comfortable Two Finger Switch**
- **3-Position Side Handle**
- **Cast Aluminum Gear Housing With Conveniently Located Spindlelock**
Accessory change is fast and easy-single wrench operation.
- **Spiral Bevel Gears**
For optimum motor torque transfer, improved performance and durability. Replaceable armature pinion gear.
- **Outstanding Durability And Performance**
Epoxy coated field windings and armature. gear case is specially sealed. Long lasting brushes.
- **Heavy-Duty Tool Rest Cast in the Gear Case**
- **Optimum Speed For Various Accessories**
Including resin bonded abrasives, wire brushes, resin fiber discs and abrasive flap discs.

EXCLUSIVE 6082-20 FEATURES

- **9-Position Rotating Main Grip**
Provides optimum comfort when grinding or cutting in any position.



SPECIFICATIONS

CATALOG NUMBER	SPEED RPM	DISC DIA.	VOLTS AC-DC	AMPS	CORD	DOUBLE INSULATED /GROUNDED	SWITCH LOCK	GUARD	LENGTH	NET WGT. LBS.	SHIP. WGT. LBS.
6080-20	6000	7"/9"	120	15.0	FIXED	DOUBLE INSULATED	N/A	OPTIONAL	19-1/4"	11.8	14.7
6081-20	6000	7"/9"	120	15.0	FIXED	GROUNDED	N/A	OPTIONAL	19-1/4"	11.8	14.7
6082-20	6000	7"/9"	120	15.0	FIXED	DOUBLE INSULATED	N/A	OPTIONAL	19-1/4"	11.8	14.7

STANDARD EQUIPMENT: Side Handle and Nylon Washer.