



HEAVY-DUTY 7" AND 9" POLISHERS

5460-6 7"/9"

• FOR USE WITH STANDARD LIQUID POLISHES



5540 7"

• FOR USE WITH HIGH SPEED STANDARD LIQUID MACHINE POLISHES



5455 7"/9"

• FOR USE WITH STANDARD LIQUID POLISHES
• SINGLE SPEED



Pads sold separately.

- Spindle Lock For Convenient Accessory Change
- Self-Stopping Long Life Brush System
- Powerful MILWAUKEE Built 11.0 Amp Motor
- Helical Gearing
- All Ball and Roller Bearings
- Aluminum Gear Case with Protective Urethane Bumper

5460-6 AND 5540 ADDITIONAL FEATURES:

- Dial Speed Control
Exclusive MILWAUKEE electronic speed control in powerful 11.0 amp polishers – ideal for clearcoat finishes.
- 10' 2-Wire Quik-Lok® Cord Set Included
Cord No. 48-76-5010. Quick detachment from tool for tangle-free carrying and storage. Instant field repair.

SPECIFICATIONS

CATALOG NUMBER	PAD DIA.	VOLTS	AMPS	SPEED (NO LOAD) RPM	SPINDLE THREAD SIZE	LENGTH ◊	NET WGT. LBS.	SHIP. WGT. LBS.
5460-6	7"/9"	120 AC	11.0	0-1750	5/8"-11	16-1/2"	8.8	12.0
5540	7"	120 AC	11.0	0-2800	5/8"-11	16-1/2"	8.8	12.0
5455	7"/9"	120 AC/DC	11.0	1750	5/8"-11	16-1/2"	8.8	11.8

STANDARD EQUIPMENT: FOR 5460-6 AND 5540 – Includes side handle, one 7" rubber backing pad, 10' 2-wire Quik-Lok® cord, disc nut and nylon washer. **FOR 5455** – Includes side handle, one 7" rubber backing pad, disc nut and nylon washer.

◊ Overall length of tool only—not including pad

ACCESSORIES

Fast, convenient hook and loop attachment – No disc nut necessary. Change pads in seconds. Foam pads are ideal for use with 5460-6 and 5540 speed control polishers on low speed for clearcoat finishes.

Traditional elastic hem and tie attachment, these pads and bonnets require the appropriate molded rubber-backing pad. (49-36-2500 or 49-36-2200)



HOOK AND LOOP FOAM PADS



HOOK AND LOOP BLENDED WOOL PADS



HOOK AND LOOP BACKING PAD
49-36-2150
(Includes Centering Tool)



CENTERING TOOL
49-67-0130
(When Purchased Separately)



BLENDED WOOL PADS



4-PLY TWISTED 100% WOOL



LAMBSWOOL BONNETS



MOLDED RUBBER BACKING PAD

DISC NUT 49-40-0390
Standard equipment.

7" DIAMETER
49-36-2500

NYLON WASHER 45-88-8465
For easier removal. (Standard equipment.)

8-1/2" DIAMETER
49-36-2200

HOOK AND LOOP FOAM PADS AND BLENDED WOOL PADS

Foam pads are designed specifically for clearcoat finishes. Run cooler and are less likely to create swirl marks. (Not recommended for inexperienced operators). Blended wool pads run cooler than 100% wool and add a margin of safety when used on clearcoat finishes.

CATALOG NUMBER	DESCRIPTION	DIAMETER	DEPTH OF PILE	APPLICATION
49-36-0650	FOAM PAD	8"	2"	High gloss finish on clearcoat
49-36-1550	FOAM PAD	8"	2"	Compounding deep cleaning on clearcoat
49-36-0600	BLENDED WOOL PAD	7-1/2"	1-1/2"	High gloss finish on clearcoat
49-36-1500	4-PLY TWISTED 100% WOOL PAD	7-1/2"	1-1/2"	Compounding deep cleaning on non-clear or clearcoat

WOOL AND BLENDED WOOL PADS / BLENDED WOOL BONNETS

100% woolen yarn polishing pads recommended for compounding, blending and polishing. Blended wool pads and bonnets recommended for high gloss finishing.

CATALOG NUMBER	DESCRIPTION	DIAMETER	DEPTH OF PILE	APPLICATION
49-36-0500	BLENDED WOOL PAD	7-1/2"	1-1/2"	High gloss finish on clearcoat
49-36-0700	BLENDED WOOL PAD	9"	1-1/2"	High gloss finish on clearcoat
49-36-1450	4-PLY TWISTED 100% WOOL PAD	7-1/2"	1-1/2"	Compounding deep cleaning
49-36-1455	4-PLY TWISTED 100% WOOL PAD	7-1/2"	2"	Compounding deep cleaning
49-36-1600	4-PLY TWISTED 100% WOOL PAD	9"	1-1/2"	Compounding deep cleaning
48-48-0500	LAMBSWOOL BONNET	7"	1-1/2"	High gloss finish on clearcoat
48-48-1000	LAMBSWOOL BONNET	9"	1-1/2"	High gloss finish on clearcoat