- · High capacity 3Ah Li-ion battery pack
- Compact size (LxHxW): 9-51/64" x 10-3/64" x 2-33/64"
- . Light weight (incl. battery): 5.1 lbs.
- . Blow Rate per Minute(Rotation with hammering): 0-4,000 bpm
- Speed at No load (Rotation only): 0-1,000 rpm
- · Clutch torque (approx): 13 in.lbs.- 48.7 in.lbs.

(8.8 in.lbs. per stage, total 5 stage)

- · Complete concrete anchor installation by one tool
- · High speed concrete drilling by air type (Cup piston method) hammer
- One hand operation
- · Dual function rotary hammer or drill & driver
- · Hammering force: 21.6 kN
- · Slow start switch for accurate drilling with a clean finish
- · Bit adapter (EY9HX403E) as standard equipment
- 1/2" SDS-plus bit system
- . Charging Time (using EY0L80B charger)*: Usable: 35 minutes Full: 50 minutes
- · Electronic performance monitoring system
- LED work light
- · With an extra battery pack as standard equipment

Typical Application

- · Lighting equipment installation
- · Conduit pipe installation
- Switch box installation

REVOLITHIUM



Drilling mode







Bit adaptor (standard) SDS-Plus shank compatible EY9HX403E



Max. Wood Screws dia.11/64" Max. Drill Diameter in Metal dia.1/2" Metal Holesaw dia.53/64" in Wood dia.45/64"



5 torque levels available

The torque level can be adjusted according to the hardness of the material or the type of material being drilled.

<Drilling mode>



Drilling can be done with one hand only!

The front and rear of the tool are well balanced for easy up, down or sideways movements.



Easy to hold, resists fatigue!



Hammer mode



Drilling Capacity in concrete SDS dia.1/8" x dia.5/8" (dia.15/32" - dia.5/8")*

*For work that can be completed with 1 battery pack.

Air-Coupling Hammer Mechanism Quick hole drilling in hard concrete!



User Friendly Features



Shoulder strap



White LED light



Tool case