

· High capacity 3.5Ah Ni-MH battery

Compact size (LxHxW): 9-15/16" x 9-9/16" x 2-1/2"

. Light weight (incl. battery): 5.9 lbs.

High performance as regular drill: Max.torque 425 in.lbs.

Max.capacity dia.2" with low speed

• Variable speed control/reversible: Low 75-450 rpm High 250-1,550 rpm

· Clutch Torque (approx): 18-106 in.lbs. (6.2 in.lbs per stage, total 15 stage) (max.torque at drilling position-stage 16)

High speed masonry drilling: Max.1,550 rpm/28,000 bpm

• Blows Rate per Minute: Low 1,350-8,100 bpm High 4,500-28,000 bpm

• Spindle Thread: 1/2"-20

• 1/2" heavy-duty keyless chuck

· Sure grip support handle

· New ergonomic balanced tool body

. Charging Time (using EY0110B charger)\*: 65 minutes

· With an extra battery pack as standard equipment

• Max. Drill Diameter: in Metal dia.1/2"

in Wood dia.2'

in Mortar/Brick dia.1/2"

## Typical Application

- Electricians
- General construction
- · Interior installation · Heating, water &
- sanitation technicians
- Masonry drilling
- Masonry/Wood fastening
  Wood/Metal drilling



## EY6932GQKW Cordless 1/2" Hammer Drill & Driver Kit

· High capacity 3.5Ah Ni-MH battery

Compact size (LxHxW): 9-5/16" x 8-7/8" x 2-9/32"

. Light weight (incl. battery): 5.3 lbs.

· High performance as regular drill: Max.torque 286 in.lbs.

Max.capacity dia.1-3/8" with low speed

 Variable speed control/reversible: Low 80-550 rpm High 300-2,000 rpm

Clutch Torque (approx): 8.7, 13.0, 21.7, 30.4, 39.0 in.lbs.(5 stage)

High speed masonry drilling: Max.2,000 rpm/30,000 bpm

• Blows Rate per Minute: Low 1,200-8,250 bpm High 4,500-30,000 bpm

• Spindle Thread: 3/8"-24

• 1/2" heavy-duty keyless chuck

. Charging Time (using EY0110B charger)\*: 55 minutes

· With an extra battery pack as standard equipment

## Typical Application

- Electricians
- General construction
- Interior installation
- · Heating, water & sanitation technicians
- · Masonry drilling · Masonry/Wood fastening
- Wood/Metal drilling

