

Impact Driver / Impact Wrench Capacity Table

Voltage		14.4V		12V		
Model No.		EY7540LN2L	EY7541LN2L	EY7202GQW	EY7206GQW	EY6506NQKW
Wood Screws in Yellow Pine	dia.1.1/64"x 2-61/64"	290	290	—	—	—
	dia.7/32"x 2-3/8"	—	—	100	100	75
	dia.5/32"x 1/2"	—	—	345	345	300
Self-Drilling Screws in SPC	*t=1/16", dia.5/32"x 1/2"	460	460	340	340	330
Bolt/ Nuts	M8 Tightened for 1 sec.	—	—	325	325	340
Standard Tensil Bolt	t=3/8", M16 x 63/64"	390	390	—	—	—
	t=3/8", M12 x 63/64"	1,000	—	—	—	—
Standard Tensil Bolt (Metal Sheet)	t=3/8", M14 x 63/64"	—	550	—	—	—
High Tensil Bolt	t=3/8", M12 x 63/64"	170	170	—	—	—

Multi Drill & Driver Capacity Table

15.6V EY6535GQW/EY6535GQWA

				per charge
DD Mode	With 1/2" keyless chuck	Drilling into Wood	dia.1" x 1-1/2"	95 holes
		Drilling into Metal (SPC/Sheet Metal)	16 gauge, dia.1/2"	58 holes
	With quick change 1/4" hex. drive	Wood Screw	#8 x 1"	825 pcs
Impact Mode	With 1/2" square drive with ball detent	Lag Bolt	dia. 3/8" x 1-15/16"	64 pcs
		Carriage Bolt & Nut	M12	150 pcs
	With quick change 1/4" hex. drive	Self-Drilling Screw	SPC/Sheet metal: t*=14 gauge, dia. 3/16"	500 pcs

14.4V EY7542LN2L

				per charge
DD Mode	Holes in Sheet Metal	t=1/16", dia.53/64"		25 pcs
		Holes in Yellow Pine	t=25/32", dia.19/32"	300 pcs
Impact Mode	Wood Screws in Yellow Pine	dia.5/32" x 61/64"		220 pcs
		Self-Drilling Screw (SPC/Sheet Metal)	t=3/32", dia.5/32" x 1/2"	300 pcs

Drill and Driver Capacity Table

Voltage		21.6V	18V	15.6V			14.4V	12V			3.6V	2.4V	
Catalog No.		EY7460LN2S	EY6450GQKW	EY6432GQKW	EY6432NQKW	EY6432FQKW	EY7440LN2L	EY6409GQKW	EY6409NQKW	EY6405FQKW	EY7410LA2S	EY6220B	EY503B
Wood Screws in Yellow Pine	dia.5/32"x 3"	700	765	—	—	—	—	—	—	—	—	—	—
	dia.5/32"x 1"	—	—	—	—	—	700	610	525	350	—	—	—
	dia.1/4"x 2-1/2"	—	—	555	480	320	385	—	—	—	—	—	—
	dia.1/8"x 3/4"	—	—	—	—	—	—	—	—	—	—	100	100
	dia.1/8"x 1/2"	—	—	—	—	—	—	—	—	—	600	—	—
Self-Drilling Screws in SPC	*t=3/64", dia.1/8"x 1/2"	960	1,360	—	—	—	—	860	730	480	—	—	—
Holes in Yellow Pine	*t=1-1/2", dia.1-27/64"	220	165	135	120	80	90	—	—	—	—	—	—
Holes in Sheet Metal	*t=1/16", dia.1/2"	180	95	—	—	—	—	—	—	—	—	—	—
Holes in SPC	*t=3/64", dia.5/54"	—	—	—	—	—	—	—	—	—	85	—	—

Rotary Hammer Drill & Driver Capacity Table 14.4V EY7840LN2S

Drilling + Fastening	Concrete screw	Holes in Concrete and Screws Fastening	dia. 1/8" x 1-3/16"	85
			dia. 5/32" x 1"	
Drilling	Plastic anchor fastening application	Holes in Concrete and Screws Fastening	dia. 15/64" x 1-3/16"	75
			dia. 11/64" x 1"	
	Holes in Concrete	dia. 1/8" x 1-3/16"	100	
		dia. 15/64" x 1-3/16"	80	
			dia. 3/8" x 1-37/64"	35
			dia. 1/2" x 1-37/64"	25