

· High capacity 3 Ah Li-ion battery

Compact size (LxHxW): 10-5/8" x 6-31/32" x 2-31/64"

· Light weight: 4.8 lbs.

· Low handle position: height 6-31/32"

• Strokes per minute: 0-2,400/min

. Length of stroke: 25/32"

Cutting performance: in wood dia.9/16", in mild steel dia.15/64" in aluminium dia.3/8"

- · Low vibration: Counter balance mechanism
- · Ergonomic design for comfortable cutting
- · 4 stage pendulum action
- Cutting angle adjustment (0°-45°)
- · Air blow function keeps cutting line clear
- Charging Time (using EY0L80B charger)*: Usable: 35 minutes Full: 50 minutes
- Electronic Performance Monitoring System
- LED work light
- . Max.thickness of mounting blade: 0.05"

Typical Application

• General construction • Carpentry

EY4541X: Battery pack and battery charger are not included.





Use with vacuum cleaner to collect dust




Cutting Circles



Cutting Angle adjustment (0°-45°)

Low-vibration design with a low center of gravity for stable cutting work



makes your work
easier with a low
center of gravity
that allows for
easy handling and
damping of
vibrations that
occur during cutting.



Dust Cover

Reduces the amount of dust ejected onto your face and into the surrounding area when working in high locations or using the tool above your head



White LED light

Counter Balance Mechanism